

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	REVISED PER ECO 13-001843.	08FEB2013	MGM	CT

SINGLE POLARIZATION

DOUBLE POLARIZATION

THREE KEY POLARIZATION

CAVITY IDENTIFICATION WHEN VIEWED FROM REAR OF CONNECTOR

1 THE PART IS MARKED WITH THE TE PART NUMBER, CHINA, DATE CODE AND LOT ID.

2. DWV RATING: 725VAC @ SEA LEVEL

3. WIRE SIZE: 24 AWG MAX

4. WORKING TEMPERATURE: -55°C ~ +125°C

5 MATERIAL:
 CONTACT : COPPER ALLOY
 SHELL : COPPER ALLOY
 INSULATOR : PEEK

6 FINISH
 CONTACT: GOLD OVER NICKEL
 SHELL : BLACK CHROMIUM

7 ALL TOLERANCES TO BE ±0.20 MM UNLESS NOTED

CHROMIUM-BLACK	THREE	SOLDERING	ø9	10	11	33.45	ø12	ø14.9	2	2157376-3
CHROMIUM-BLACK	DOUBLE	SOLDERING	ø9	10	11	33.45	ø12	ø14.9	2	2157376-2
CHROMIUM-BLACK	SINGLE	SOLDERING	ø9	10	11	33.45	ø12	ø14.9	2	2157376-1
FINISH	POLARIZATION	TERMINATION	A	Q	S	L max	d	D	SHELL SIZE	TE PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C THOMAS 24FEB2011		TE Connectivity		
DIMENSIONS: mm		CHK R. GROSS 24FEB2011				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R. GROSS 24FEB2011				
0 PLC ± - 1 PLC ± - 2 PLC ± 0.20 3 PLC ± - 4 PLC ± - ANGLES ± 3°		NAME CIRCULAR HD PLUG WITH PIN CONTACTS 8 POS.				
MATERIAL		PRODUCT SPEC 108-127005	SIZE A2	CAGE CODE 00779	DRAWING NO C=2157376	RESTRICTED TO
FINISH		APPLICATION SPEC	SCALE NTS	SHEET 1 of 1	REV C	
CUSTOMER DRAWING		WEIGHT				

1471-9 (3/11)

2157376