



THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	20
© COPYRIGHT 20	BY -	ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

- NOTES:
1. MATERIALS AND FINISH
HOUSING: PA 6-6, UL 94-V0, COLOR GREEN.
CLAMP: BRASS, NICKEL PLATED.
TERMINAL: BRASS, TIN PLATED.
CLAMPING SCREW: M3, BRASS, NICKEL PLATED.
2. MECHANICAL
WIRE STRIPPING LENGTH : 5.0-6.0 mm
MIN. PC BOARD HOLES DIAMETER : 1.1 mm
MAX. PC BOARD THICKNESS : 2.4 mm
RECOMMENDED TIGHTENING TORQUE FOR SCREW : 0.5 Nm.
3. ELECTRICAL
WIRE RANGE : 16-30 AWG
MAX. VOLTAGE : 300 V
MAX CURRENT : 13.5 A
CONTACT RESISTANCE : <15 m Ohm
INSULATION RESISTANCE : >1000 M Ohm (500V DC)
4. RECOGNIZED UNDER THE COMPONENT PROGRAM OF
UNDERWRITERS LABORATORIES INC., FILE NO E60677.
5. OPERATING TEMPERATURE RANGE: -40°C TO +110°C

 NOT CUMULATIVE TOLERANCE.

7. PACKED IN BOX.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN E. ZANOLINI	26APR2001	 TE Connectivity							
DIMENSIONS: mm		CHK D. BIEVENOUR	26APR2001	NAME TERMINAL BLOCK, PCB MOUNT TOP ENTRY WIRE, STACKING W/INTERLOCK, 5.08mm PITCH							
		APVD D. BIEVENOUR	26APR2001								
		PRODUCT SPEC						SIZE A 3			
		108-20166									
		APPLICATION SPEC									
MATERIAL SEE NOTES		114-20079		CAGE CODE 00779		DRAWING NO C-284094		RESTRICTED TO			
		WEIGHT -									
FINISH SEE NOTES		CUSTOMER DRAWING		SCALE 1:1		SHEET 2 OF 2		REV F			