

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.


LOC	DIST
F	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D3	REVISED PER ECO-20-004274	01APR2020	SM	DR








1. TOOLS:
   - TERMINAL: DIE: NEST PN 1-1490413-7 + INDENTER PN 1490414-2
     FOR TOOL OR HEAD NUMBER, SEE INSTRUCTION SHEET 408-8691
   - INSULATION SLEEVE: CRIMPING HEAD PN 69099, DIE PN 69214-1 (INSTRUCTION SHEET 408-1826)
   (OUTILLAGE:
   - COSSE: MATRICE: EMPREINTE PN 1-1490413-7 + PN 1490414-2
     POUR LES REFERENCES D'OUTILS ET DE TETE DE SERTISSAGE, VOIR INSTRUCTION SHEET 408-8691
   - MANCHON ISOLANT: TETE DE SERTISSAGE PN 69099, MATRICE 69214-1 (INSTRUCTION SHEET 408-1826))

2. WIRE DIMENSIONS: 34,500 mm^2 [1.358 IN^2], INSULATION DIAMETER 11.000 mm [0.433 IN]
   (DIMENSION DU FIL: 34,500 mm^2 [1.358 IN^2], DIAMETRE ISOLANT 11.000 mm [0.433 IN])

△3 PERMISSIBLE TONGUE DISTORTION: 2,700 mm [0.106 IN] MAX
(DEFORMATION DE LA PLAGE AUTORISEE: 2,700 mm [0.106 IN] MAX HORS TOUT)

△4 MATERIALS AND FINISH:
- TERMINAL: COPPER,PER ASTM B152
- FINISH: NICKEL PLATE 0.00762 [.000300]
  MIN EXT THK PER SAE AMS QQ-N-290
- INSULATION SLEEVE: PTFE
  (MATIERES ET FINITION:
- COSSE: CUIVRE, FINITION: NICKEL
- MANCHON: PTFE)

△5 STAMP AMP 2W* 60-75 APPROX AS SHOWN



10	LOOSE PIECE	133042-1
QTY	PACKAGE TYPE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm/INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±0.127[.005]
4 PLC ±-
ANGLES ±-

MATERIAL △4
FINISH △4

DWN JJ. DESPRETZ 28AUG2003
CHK G-ROBERT -
APVD Y-PETRONIN -
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME KIT, POST INSULATED STRATO-THERM, WIRE SIZE: 2 AWG, 90 BEND TERMINAL
-

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-133042	

CUSTOMER DRAWING | SCALE 2:1 | SHEET 1 OF 1 | REV D3