

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		RELEASED PER ECO-16-004435	15APR2016	KG EO

MATING FACE

REAR FACE

1 FRONT & REAR INSULATOR: HIGH-TEMP THERMOPLASTIC OR THERMOSET EPOXY PER ASTM D5948.
 CONTACT RETENTION CLIPS: STAINLESS STEEL PER AISI 302 OR COPPER ALLOY PER ASTM B194
 REAR GROMMET & INTERFACIAL SEAL: FLUOROSILICONE ELASTOMER PER MIL-R-25988 B, EXCEPT 4.6.6.1

2 DATE CODE: YEAR & WEEK (YY WW)

3. DESCRIPTIVE PART NUMBER GPRBE14PA
 THIS INSERT CONTAINS: 14 CAVITIES FOR SIZE 16 PIN CONTACTS.

4. THIS PRODUCT IS SOLD BY TE CONNECTIVITY UNDER A LICENSE FROM RADIALL SA.

617999249	1738116-1
RADIALL PART NUMBER	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN BH	29 JUN 2006	TE Connectivity	
DIMENSIONS:		CHK	29 JUN 2006		
mm		APVD	29 JUN 2006		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC			
0 PLC ±		APPLICATION SPEC		NAME	INSERT ASSEMBLY, PIN, ENVIRONMENTAL, ARRANGEMENT 14, KEY A, GPRB
1 PLC ±0.1		WEIGHT		SIZE	A200779
2 PLC ±0.05		CUSTOMER DRAWING		CAGE CODE	C-1738116
3 PLC ±		SCALE	4:1	DRAWING NO	
4 PLC ±		SHEET	OF	RESTRICTED TO	
ANGLES ±1		REV	A		
FINISH					

1471-9 (3/13)