
THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
AF	50

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	ECR-15-005665	10AUG2015	BDA	PKS





IDENTIFICATION NUMBER 15
FOR MAGNET WIRE RANGE


1 CONTINUOUS STRIP ON REELS WITH TERMINALS LOCATED ON 5.59±0.08 [.220±.003] CENTERS.

2 SLOT ACCEPTS A SINGLE WIRE MAX OF 0.60–0.85mm [#22.5–#19.5] AWG COPPER MAGNET WIRE.
SLOT ACCEPTS A SINGLE WIRE MAX OF 0.72–0.91mm [#21–#19] AWG ALUMINUM MAGNET WIRE.
ALUMINUM WIRE RANGE APPLIES FOR POST-TIN PLATED VERSIONS ONLY.

3 AFTER INSERTION INTO PLASTIC HOLDER TAB PORTION MUST BE BENT OVER 45° TO 90° OR POTTED-IN TO PREVENT PULL-OUT WHEN MATING RECEPTACLE IS DISCONNECTED.







1742995

1742995-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN WRP 22NOV12	TE Connectivity
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – ; 1 PLC ± – ; 2 PLC ± 0.25[.010] ; 3 PLC ± – ; 4 PLC ± – ; ANGLES ± –	CHK MF 22NOV12	NAME TAB, 4.75[.187] FASTON,™ 300 SERIES MAG-MATE™ –
		APVD MYH 22NOV12	
		PRODUCT SPEC 108-2012	
		APPLICATION SPEC 114-2046	SIZE A2 · CAGE CODE 00779 · DRAWING NO C-1742995 · RESTRICTED TO –
MATERIAL 082 PRE-MILLED BRASS	FINISH 0.002032[.000080] MIN TIN	WEIGHT –	CUSTOMER DRAWING · SCALE 10:1 · SHEET 1 OF 1 · REV A2