

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT - By -

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
P1		CUTTING BURR DETAILS ADDED	07SEP2018	RK	PS

- MATERIAL:
HOUSING: POLYAMIDE 6, UL94V-2.
COLOR: NATURAL (OFF WHITE).
TUBULAR CONTACT: BRASS, TIN PLATED.
SCREW: M3, STEEL, ZINC PLATED W/ NON-
HEXAVALENT CHROMATE (CHROME III).
WIRE PROTECTION: STAINLESS STEEL.
- ELECTRICAL:
CURRENT RATING: 30A, 250V, 10-22 AWG.
CURRENT RATING: 25A, 250V, 12-24 AWG.
WIRE RANGE: 10-24 AWG.
- ENVIRONMENTAL:
CONTINUOUS WORKING TEMP.: -35°C TO +100°C.
- CUTTING PROJECTION CAN BE ON BOTH SIDES
DEPENDING ON CUTTING LOCATION
- CUTTING BURR MAX. 1mm ALLOWED.

1776296-4 AS SHOWN

100.0	116.6	TSB500 1231DS	1-1776296-2
90.0	106.6	TSB500 1131DS	1-1776296-1
80.0	96.6	TSB500 1031DS	1-1776296-0
70.0	86.6	TSB500 0931DS	1776296-9
60.0	76.6	TSB500 0831DS	1776296-8
50.0	66.6	TSB500 0731DS	1776296-7
40.0	56.6	TSB500 0631DS	1776296-6
30.0	46.6	TSB500 0531DS	1776296-5
20.0	36.6	TSB500 0431DS	1776296-4
10.0	26.6	TSB500 0331DS	1776296-3
-	16.6	TSB500 0213DS	1776296-2
-	6.6	TSB500 0131DS	1776296-1
DIM B	DIM A	T & B PART NUMBER	TE PART NUMBER

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		S CHLEGEL		3/18/05		TE Connectivity Ltd.	
mm		0 PLC	± -	CHK	C RICHARD	3/18/05					
		1 PLC	± 0.3	APVD	C RICHARD	3/18/05		NAME			
		2 PLC	± 0.25	PRODUCT SPEC		EUROPA TERMINAL BLOCK W/WIRE PROTECTOR					
		3 PLC	± -	APPLICATION SPEC		MOUNTING HOLES DIA 3.1, 10mm PITCH					
		4 PLC	± -	WEIGHT		-		SIZE		RESTRICTED TO	
MATERIAL		FINISH		SEE NOTES		SEE NOTES		CAGE CODE		DRAWING NO	
SEE NOTES		SEE NOTES		CUSTOMER DRAWING		SCALE		SHEET		REV	
						NTS		1 of 1		P1	

1470-19 (1/15)