

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 87232 ,87232
© COPYRIGHT 87232 By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER ECO-14-014168	01OCT2014	NK	MM





4	39	101.19 [3.984]	40	4-2267063-0
6 4	38	98.65 [3.884]	39	3-2267063-9
6 4	37	96.11 [3.784]	38	3-2267063-8
6 4	36	93.57 [3.684]	37	3-2267063-7
6 4	35	91.03 [3.584]	36	3-2267063-6
6 4	34	88.49 [3.484]	35	3-2267063-5
6 4	33	85.95 [3.384]	34	3-2267063-4
6 4	32	83.41 [3.284]	33	3-2267063-3
6 4	31	80.87 [3.184]	32	3-2267063-2
6 4	30	78.33 [3.084]	31	3-2267063-1
6 4	29	75.79 [2.984]	30	3-2267063-0
6 4	28	73.25 [2.884]	29	2-2267063-9
6 4	27	70.71 [2.784]	28	2-2267063-8
6 4	26	68.17 [2.684]	27	2-2267063-7
6 4	25	65.63 [2.584]	26	2-2267063-6
6 4	24	63.09 [2.484]	25	2-2267063-5
6 4	23	60.55 [2.384]	24	2-2267063-4
6 4	22	58.01 [2.284]	23	2-2267063-3
6 4	21	55.47 [2.184]	22	2-2267063-2
6 4	20	52.93 [2.084]	21	2-2267063-1
4	19	50.39 [1.984]	20	2-2267063-0
6 4	18	47.85 [1.884]	19	1-2267063-9
4	17	45.31 [1.784]	18	1-2267063-8
6 4	16	42.77 [1.684]	17	1-2267063-7
6 4	15	40.23 [1.584]	16	1-2267063-6
6 4	14	37.69 [1.484]	15	1-2267063-5
6 4	13	35.15 [1.384]	14	1-2267063-4
6 4	12	32.61 [1.284]	13	1-2267063-3
4	11	30.07 [1.184]	12	1-2267063-2
4	10	27.53 [1.084]	11	1-2267063-1
4	9	24.99 [.984]	10	1-2267063-0
4	8	22.45 [.884]	9	2267063-9
4	7	19.91 [.784]	8	2267063-8
4	6	17.37 [.684]	7	2267063-7
4	5	14.83 [.584]	6	2267063-6
4	4	12.29 [.484]	5	2267063-5
4	3	9.75 [.384]	4	2267063-4
4	2	7.21 [.284]	3	2267063-3
4	1	4.67 [.184]	2	2267063-2
4	0	2.13 [.084]	1	2267063-1
FINISH	B	A	NO OF POSN	PART NUMBER

1 RECOMMENDED MOUNTING HOLE: ø0.89±0.08[.035±.003].

2 POINT OF MEASUREMENT FOR PLATING THICKNESS.

3 HOUSING: GLASS FILLED NYLON. COLOR – BLACK.
POSTS: PHOS. BRONZE

4 0.00076[.000030] GOLD IN CONTACT AREA, MATTE TIN
REMAINDER OF POSTS, ALL OVER 0.00127[.000050] NICKEL.

5 0.00007[.000003] GOLD OVER 0.00068[.000027] Pd/Ni IN CONTACT AREA, MATTE TIN
REMAINDER OF POSTS, ALL OVER 0.00127[.000050] NICKEL.

6 PRELIMINARY PART NUMBER NOT RELEASED FOR PRODUCTION.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± 0.13[.005]
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL 3

FINISH 4

DWN NAGALAKSHMI K 03FEB2014
CHK MILLER MICHAEL 03FEB2014
APVD MILLER MICHAEL 03FEB2014
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME HEADER ASSEMBLY, MOD II,
2.54[.100] CL, RIGHT ANGLE,
0.64[.025] SQUARE POST, SINGLE ROW

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-2267063	—

CUSTOMER DRAWING | SCALE 5:1 | SHEET 1 OF 2 | REV A

2267063

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 87232 ,87232
© COPYRIGHT 87232 By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

5	39	101.19 [3.984]	40	9-2267063-0
6 5	38	98.65 [3.884]	39	8-2267063-9
6 5	37	96.11 [3.784]	38	8-2267063-8
6 5	36	93.57 [3.684]	37	8-2267063-7
6 5	35	91.03 [3.584]	36	8-2267063-6
6 5	34	88.49 [3.484]	35	8-2267063-5
6 5	33	85.95 [3.384]	34	8-2267063-4
6 5	32	83.41 [3.284]	33	8-2267063-3
6 5	31	80.87 [3.184]	32	8-2267063-2
6 5	30	78.33 [3.084]	31	8-2267063-1
6 5	29	75.79 [2.984]	30	8-2267063-0
6 5	28	73.25 [2.884]	29	7-2267063-9
6 5	27	70.71 [2.784]	28	7-2267063-8
6 5	26	68.17 [2.684]	27	7-2267063-7
6 5	25	65.63 [2.584]	26	7-2267063-6
6 5	24	63.09 [2.484]	25	7-2267063-5
6 5	23	60.55 [2.384]	24	7-2267063-4
6 5	22	58.01 [2.284]	23	7-2267063-3
6 5	21	55.47 [2.184]	22	7-2267063-2
6 5	20	52.93 [2.084]	21	7-2267063-1
5	19	50.39 [1.984]	20	7-2267063-0
6 5	18	47.85 [1.884]	19	6-2267063-9
5	17	45.31 [1.784]	18	6-2267063-8
6 5	16	42.77 [1.684]	17	6-2267063-7
6 5	15	40.23 [1.584]	16	6-2267063-6
6 5	14	37.69 [1.484]	15	6-2267063-5
6 5	13	35.15 [1.384]	14	6-2267063-4
6 5	12	32.61 [1.284]	13	6-2267063-3
5	11	30.07 [1.184]	12	6-2267063-2
5	10	27.53 [1.084]	11	6-2267063-1
5	9	24.99 [.984]	10	6-2267063-0
5	8	22.45 [.884]	9	5-2267063-9
5	7	19.91 [.784]	8	5-2267063-8
5	6	17.37 [.684]	7	5-2267063-7
5	5	14.83 [.584]	6	5-2267063-6
5	4	12.29 [.484]	5	5-2267063-5
5	3	9.75 [.384]	4	5-2267063-4
5	2	7.21 [.284]	3	5-2267063-3
5	1	4.67 [.184]	2	5-2267063-2
5	0	2.13 [.084]	1	5-2267063-1
FINISH	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± 0.13[.005]
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL

FINISH

DWN NAGALAKSHMI K 03FEB2014
CHK MILLER MICHAEL 03FEB2014
APVD MILLER MICHAEL 03FEB2014
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
HEADER ASSEMBLY, MOD II,
2.54[.100] CL, RIGHT ANGLE,
0.64[.025] SQUARE POST, SINGLE ROW

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-2267063	—

CUSTOMER DRAWING | SCALE 5:1 | SHEET 2 OF 2 | REV A

2267063