
THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
AD	39

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED PER ECO-14-014168	01OCT2014	NK	MM



1 POINT OF MEASUREMENT FOR PLATING THICKNESS.


2 THE TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.

3 PRELIMINARY PART NUMBER NOT RELEASED FOR PRODUCTION.

4 .000030 GOLD ON THE CONTACT AREA, MATTE TIN ON SOLDER AREA, ALL OVER .000050 NICKEL.

5 .000003 GOLD OVER .000027 Pd/Ni ON THE CONTACT AREA, MATTE TIN ON SOLDER AREA, ALL OVER .000050 NICKEL.

6 HOUSING: FLAME RETARDENT THERMOPLASTIC
COLOR: BLACK
POSTS: PHOS BRONZE



RECOMMENDED HOLE LAYOUT

4	3.984	3.900	39	80	4-2267065-0
3 4	3.884	3.800	38	78	3-2267065-9
3 4	3.784	3.700	37	76	3-2267065-8
3 4	3.684	3.600	36	74	3-2267065-7
3 4	3.584	3.500	35	72	3-2267065-6
3 4	3.484	3.400	34	70	3-2267065-5
3 4	3.384	3.300	33	68	3-2267065-4
3 4	3.284	3.200	32	66	3-2267065-3
3 4	3.184	3.100	31	64	3-2267065-2
3 4	3.084	3.000	30	62	3-2267065-1
4	2.984	2.900	29	60	3-2267065-0
3 4	2.884	2.800	28	58	2-2267065-9
3 4	2.784	2.700	27	56	2-2267065-8
3 4	2.684	2.600	26	54	2-2267065-7
4	2.584	2.500	25	52	2-2267065-6
4	2.484	2.400	24	50	2-2267065-5
3 4	2.384	2.300	23	48	2-2267065-4
4	2.284	2.200	22	46	2-2267065-3
3 4	2.184	2.100	21	44	2-2267065-2
3 4	2.084	2.000	20	42	2-2267065-1
4	1.984	1.900	19	40	2-2267065-0
4	1.884	1.800	18	38	1-2267065-9
3 4	1.784	1.700	17	36	1-2267065-8
4	1.684	1.600	16	34	1-2267065-7
3 4	1.584	1.500	15	32	1-2267065-6
4	1.484	1.400	14	30	1-2267065-5
3 4	1.384	1.300	13	28	1-2267065-4
4	1.284	1.200	12	26	1-2267065-3
4	1.184	1.100	11	24	1-2267065-2
4	1.084	1.000	10	22	1-2267065-1
4	.984	.900	9	20	1-2267065-0
4	.884	.800	8	18	2267065-9
4	.784	.700	7	16	2267065-8
4	.684	.600	6	14	2267065-7
4	.584	.500	5	12	2267065-6
4	.484	.400	4	10	2267065-5
4	.384	.300	3	8	2267065-4
4	.284	.200	2	6	2267065-3
4	.184	.100	1	4	2267065-2
4	.084	—	—	2	2267065-1
FINISH	C	B	A	NO OF POS	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± .005
4 PLC ± -
ANGLES ± -

MATERIAL 6

FINISH 4

DWN NAGALAKSHMI K 03FEB2014
CHK MILLER MICHAEL 03FEB2014
APVD MILLER MICHAEL 03FEB2014
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME ASSEMBLY, MOD II, HEADER, DOUBLE ROW, .100 X .100 CL. VERTICAL, .025 SQUARE POSTS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-2267065	—

CUSTOMER DRAWING | SCALE — | SHEET 1 OF 2 | REV A

2267065

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
AD	39

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

	5	3.984	3.900	39	80	9–2267065–0
3	5	3.884	3.800	38	78	8–2267065–9
3	5	3.784	3.700	37	76	8–2267065–8
3	5	3.684	3.600	36	74	8–2267065–7
3	5	3.584	3.500	35	72	8–2267065–6
3	5	3.484	3.400	34	70	8–2267065–5
3	5	3.384	3.300	33	68	8–2267065–4
3	5	3.284	3.200	32	66	8–2267065–3
3	5	3.184	3.100	31	64	8–2267065–2
3	5	3.084	3.000	30	62	8–2267065–1
	5	2.984	2.900	29	60	8–2267065–0
3	5	2.884	2.800	28	58	7–2267065–9
3	5	2.784	2.700	27	56	7–2267065–8
3	5	2.684	2.600	26	54	7–2267065–7
	5	2.584	2.500	25	52	7–2267065–6
	5	2.484	2.400	24	50	7–2267065–5
3	5	2.384	2.300	23	48	7–2267065–4
	5	2.284	2.200	22	46	7–2267065–3
3	5	2.184	2.100	21	44	7–2267065–2
3	5	2.084	2.000	20	42	7–2267065–1
	5	1.984	1.900	19	40	7–2267065–0
	5	1.884	1.800	18	38	6–2267065–9
3	5	1.784	1.700	17	36	6–2267065–8
	5	1.684	1.600	16	34	6–2267065–7
3	5	1.584	1.500	15	32	6–2267065–6
	5	1.484	1.400	14	30	6–2267065–5
3	5	1.384	1.300	13	28	6–2267065–4
	5	1.284	1.200	12	26	6–2267065–3
	5	1.184	1.100	11	24	6–2267065–2
	5	1.084	1.000	10	22	6–2267065–1
	5	.984	.900	9	20	6–2267065–0
	5	.884	.800	8	18	5–2267065–9
	5	.784	.700	7	16	5–2267065–8
	5	.684	.600	6	14	5–2267065–7
	5	.584	.500	5	12	5–2267065–6
	5	.484	.400	4	10	5–2267065–5
	5	.384	.300	3	8	5–2267065–4
	5	.284	.200	2	6	5–2267065–3
	5	.184	.100	1	4	5–2267065–2
	5	.084	—	—	2	5–2267065–1
	FINISH	C	B	A	NO OF POS	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .005
4 PLC ± –
ANGLES ± –

MATERIAL

FINISH

DWN NAGALAKSHMI K 03FEB2014
CHK MILLER MICHAEL 03FEB2014
APVD MILLER MICHAEL 03FEB2014
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME ASSEMBLY, MOD II, HEADER, DOUBLE ROW, .100 X .100 CL. VERTICAL, .025 SQUARE POSTS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-2267065	—

CUSTOMER DRAWING | SCALE – | SHEET 2 OF 2 | REV A

2267065