

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ;- .
© COPYRIGHT - By: - ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECO-15-004233	18MAR2015	NK	MM





RECOMMENDED BOARD LAYOUT

△1 0.00076[.000030] GOLD ON CONTACT AREA, MATTE TIN ON SOLDER AREA, ALL OVER 0.00127[.000050] NICKEL.

△2 0.00007[.000003] GOLD OVER 0.00068[.000027] Pd/Ni ON CONTACT AREA, MATTE TIN ON SOLDER AREA, ALL OVER 0.00127[.000050] NICKEL.

△3 PRELIMINARY PART NUMBER NOT RELEASED FOR PRODUCTION.

△4 HOUSING: FLAME RETARDANT THERMOPLASTIC
COLOR: BLACK
POSTS: PHOS. BRONZE

	△1	NONE	NONE	2.79 [.110]	101.19 [3.984]	99.06 [3.900]	39	80	4-2267067-0
△3	△1	NONE	NONE	2.79 [.110]	98.65 [3.884]	96.52 [3.800]	38	78	3-2267067-9
△3	△1	NONE	NONE	2.79 [.110]	96.11 [3.784]	93.98 [3.700]	37	76	3-2267067-8
△3	△1	NONE	NONE	2.79 [.110]	93.57 [3.684]	91.44 [3.600]	36	74	3-2267067-7
△3	△1	NONE	NONE	2.79 [.110]	91.03 [3.584]	88.90 [3.500]	35	72	3-2267067-6
	△1	NONE	NONE	2.79 [.110]	88.49 [3.484]	86.36 [3.400]	34	70	3-2267067-5
△3	△1	NONE	NONE	2.79 [.110]	85.95 [3.384]	83.82 [3.300]	33	68	3-2267067-4
	△1	NONE	NONE	2.79 [.110]	83.41 [3.284]	81.28 [3.200]	32	66	3-2267067-3
	△1	NONE	NONE	2.79 [.110]	80.87 [3.184]	78.74 [3.100]	31	64	3-2267067-2
△3	△1	NONE	NONE	2.79 [.110]	78.33 [3.084]	76.20 [3.000]	30	62	3-2267067-1
	△1	NONE	NONE	2.79 [.110]	75.79 [2.984]	73.66 [2.900]	29	60	3-2267067-0
△3	△1	NONE	NONE	2.79 [.110]	73.25 [2.884]	71.12 [2.800]	28	58	2-2267067-9
	△1	NONE	NONE	2.79 [.110]	70.71 [2.784]	68.58 [2.700]	27	56	2-2267067-8
△3	△1	NONE	NONE	2.79 [.110]	68.17 [2.684]	66.04 [2.600]	26	54	2-2267067-7
△3	△1	NONE	NONE	2.79 [.110]	65.63 [2.584]	63.50 [2.500]	25	52	2-2267067-6
	△1	NONE	NONE	2.79 [.110]	63.09 [2.484]	60.96 [2.400]	24	50	2-2267067-5
△3	△1	NONE	NONE	2.79 [.110]	60.55 [2.384]	58.42 [2.300]	23	48	2-2267067-4
△3	△1	NONE	NONE	2.79 [.110]	58.01 [2.284]	55.88 [2.200]	22	46	2-2267067-3
	△1	NONE	NONE	2.79 [.110]	55.47 [2.184]	53.34 [2.100]	21	44	2-2267067-2
△3	△1	NONE	NONE	2.79 [.110]	52.93 [2.084]	50.80 [2.000]	20	42	2-2267067-1
	△1	NONE	NONE	2.79 [.110]	50.39 [1.984]	48.26 [1.900]	19	40	2-2267067-0
△3	△1	NONE	NONE	2.79 [.110]	47.85 [1.884]	45.72 [1.800]	18	38	1-2267067-9
△3	△1	NONE	NONE	2.79 [.110]	45.31 [1.784]	43.18 [1.700]	17	36	1-2267067-8
△3	△1	NONE	NONE	2.79 [.110]	42.77 [1.684]	40.64 [1.600]	16	34	1-2267067-7
△3	△1	NONE	NONE	2.79 [.110]	40.23 [1.584]	38.10 [1.500]	15	32	1-2267067-6
	△1	NONE	NONE	2.79 [.110]	37.69 [1.484]	35.56 [1.400]	14	30	1-2267067-5
	△1	NONE	NONE	2.79 [.110]	35.15 [1.384]	33.02 [1.300]	13	28	1-2267067-4
	△1	NONE	NONE	2.79 [.110]	32.61 [1.284]	30.48 [1.200]	12	26	1-2267067-3
	△1	NONE	NONE	2.79 [.110]	30.07 [1.184]	27.94 [1.100]	11	24	1-2267067-2
	△1	NONE	NONE	2.79 [.110]	27.53 [1.084]	25.40 [1.000]	10	22	1-2267067-1
	△1	NONE	NONE	2.79 [.110]	24.99 [.984]	22.86 [.900]	9	20	1-2267067-0
	△1	NONE	NONE	2.79 [.110]	22.45 [.884]	20.32 [.800]	8	18	2267067-9
	△1	NONE	NONE	2.79 [.110]	19.91 [.784]	17.78 [.700]	7	16	2267067-8
	△1	NONE	NONE	2.79 [.110]	17.37 [.684]	15.24 [.600]	6	14	2267067-7
	△1	NONE	NONE	2.79 [.110]	14.83 [.584]	12.70 [.500]	5	12	2267067-6
	△1	NONE	NONE	2.79 [.110]	12.29 [.484]	10.16 [.400]	4	10	2267067-5
	△1	NONE	NONE	2.79 [.110]	9.75 [.384]	7.62 [.300]	3	8	2267067-4
	△1	NONE	NONE	2.79 [.110]	7.21 [.284]	5.08 [.200]	2	6	2267067-3
	△1	NONE	NONE	2.79 [.110]	4.67 [.184]	2.54 [.100]	1	4	2267067-2
	△1	NONE	NONE	2.79 [.110]	2.13 [.084]	-	-	2	2267067-1
FINISH		ROW E	ROW D	Z	C	B	A	NO OF POSN	PART NUMBER
		POSTS OMITTED							

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± 0.13 [.005]
3 PLC ± -
4 PLC ± -
ANGLES ± -

MATERIAL △4

FINISH 1

DWN 04FEB2014 NAGALAKSHMI K
CHK 04FEB2014 MILLER MICHAEL
APVD 04FEB2014 MILLER MICHAEL
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME
ASSEMBLY, MOD II, DOUBLE ROW
.100 x .100 CL, RIGHT ANGLE
WITH SPANKED TAILS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	-	C-2267067	-

CUSTOMER DRAWING | SCALE 4:1 | SHEET 1 OF 2 | REV A1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – ; – .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

2	NONE	NONE	2.79 [.110]	101.19 [3.984]	99.06 [3.900]	39	80	9–2267067–0
3 2	NONE	NONE	2.79 [.110]	98.65 [3.884]	96.52 [3.800]	38	78	8–2267067–9
3 2	NONE	NONE	2.79 [.110]	96.11 [3.784]	93.98 [3.700]	37	76	8–2267067–8
3 2	NONE	NONE	2.79 [.110]	93.57 [3.684]	91.44 [3.600]	36	74	8–2267067–7
3 2	NONE	NONE	2.79 [.110]	91.03 [3.584]	88.90 [3.500]	35	72	8–2267067–6
2	NONE	NONE	2.79 [.110]	88.49 [3.484]	86.36 [3.400]	34	70	8–2267067–5
3 2	NONE	NONE	2.79 [.110]	85.95 [3.384]	83.82 [3.300]	33	68	8–2267067–4
2	NONE	NONE	2.79 [.110]	83.41 [3.284]	81.28 [3.200]	32	66	8–2267067–3
2	NONE	NONE	2.79 [.110]	80.87 [3.184]	78.74 [3.100]	31	64	8–2267067–2
3 2	NONE	NONE	2.79 [.110]	78.33 [3.084]	76.20 [3.000]	30	62	8–2267067–1
2	NONE	NONE	2.79 [.110]	75.79 [2.984]	73.66 [2.900]	29	60	8–2267067–0
3 2	NONE	NONE	2.79 [.110]	73.25 [2.884]	71.12 [2.800]	28	58	7–2267067–9
2	NONE	NONE	2.79 [.110]	70.71 [2.784]	68.58 [2.700]	27	56	7–2267067–8
3 2	NONE	NONE	2.79 [.110]	68.17 [2.684]	66.04 [2.600]	26	54	7–2267067–7
3 2	NONE	NONE	2.79 [.110]	65.63 [2.584]	63.50 [2.500]	25	52	7–2267067–6
2	NONE	NONE	2.79 [.110]	63.09 [2.484]	60.96 [2.400]	24	50	7–2267067–5
3 2	NONE	NONE	2.79 [.110]	60.55 [2.384]	58.42 [2.300]	23	48	7–2267067–4
3 2	NONE	NONE	2.79 [.110]	58.01 [2.284]	55.88 [2.200]	22	46	7–2267067–3
2	NONE	NONE	2.79 [.110]	55.47 [2.184]	53.34 [2.100]	21	44	7–2267067–2
3 2	NONE	NONE	2.79 [.110]	52.93 [2.084]	50.80 [2.000]	20	42	7–2267067–1
2	NONE	NONE	2.79 [.110]	50.39 [1.984]	48.26 [1.900]	19	40	7–2267067–0
3 2	NONE	NONE	2.79 [.110]	47.85 [1.884]	45.72 [1.800]	18	38	6–2267067–9
3 2	NONE	NONE	2.79 [.110]	45.31 [1.784]	43.18 [1.700]	17	36	6–2267067–8
3 2	NONE	NONE	2.79 [.110]	42.77 [1.684]	40.64 [1.600]	16	34	6–2267067–7
3 2	NONE	NONE	2.79 [.110]	40.23 [1.584]	38.10 [1.500]	15	32	6–2267067–6
2	NONE	NONE	2.79 [.110]	37.69 [1.484]	35.56 [1.400]	14	30	6–2267067–5
2	NONE	NONE	2.79 [.110]	35.15 [1.384]	33.02 [1.300]	13	28	6–2267067–4
2	NONE	NONE	2.79 [.110]	32.61 [1.284]	30.48 [1.200]	12	26	6–2267067–3
2	NONE	NONE	2.79 [.110]	30.07 [1.184]	27.94 [1.100]	11	24	6–2267067–2
2	NONE	NONE	2.79 [.110]	27.53 [1.084]	25.40 [1.000]	10	22	6–2267067–1
2	NONE	NONE	2.79 [.110]	24.99 [.984]	22.86 [.900]	9	20	6–2267067–0
2	NONE	NONE	2.79 [.110]	22.45 [.884]	20.32 [.800]	8	18	5–2267067–9
2	NONE	NONE	2.79 [.110]	19.91 [.784]	17.78 [.700]	7	16	5–2267067–8
2	NONE	NONE	2.79 [.110]	17.37 [.684]	15.24 [.600]	6	14	5–2267067–7
2	NONE	NONE	2.79 [.110]	14.83 [.584]	12.70 [.500]	5	12	5–2267067–6
2	NONE	NONE	2.79 [.110]	12.29 [.484]	10.16 [.400]	4	10	5–2267067–5
2	NONE	NONE	2.79 [.110]	9.75 [.384]	7.62 [.300]	3	8	5–2267067–4
2	NONE	NONE	2.79 [.110]	7.21 [.284]	5.08 [.200]	2	6	5–2267067–3
2	NONE	NONE	2.79 [.110]	4.67 [.184]	2.54 [.100]	1	4	5–2267067–2
2	NONE	NONE	2.79 [.110]	2.13 [.084]	–	–	2	5–2267067–1
FINISH	ROW E	ROW D	Z	C	B	A	NO OF POSN	PART NUMBER
	POSTS OMITTED							

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± 0.13 [.005]
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL

FINISH

DWN 04FEB2014 NAGALAKSHMI K
CHK 04FEB2014 MILLER MICHAEL
APVD 04FEB2014 MILLER MICHAEL
PRODUCT SPEC –
APPLICATION SPEC –
WEIGHT –

TE Connectivity

NAME
ASSEMBLY, MOD II, DOUBLE ROW
.100 x .100 CL, RIGHT ANGLE
WITH SPANKED TAILS

SIZE	CAGE CODE	DRAWING NO.	RESTRICTED TO
A1	–	C-2267067	–

CUSTOMER DRAWING | SCALE 4:1 | SHEET 2 OF 2 | REV A1