


1. PINS TO COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.
2. MATES WITH PLUG P/N 172167-1.
3. COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
4. RECOMMENDED FOR EDGE MOUNTING.
5. 0.00381 MIN MATTE TIN LEAD OVER 0.00127 MIN NICKEL ENTIRE LENGTH OF PIN.
6. 0.00076 MIN GOLD PLATE IN THE LOCALIZED PLATE AREA, 0.00381 MIN MATTE TIN LEAD IN THE LOCALIZED PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.
7. 0.00381 MIN MATTE TIN OVER 0.00127 MIN NICKEL ENTIRE LENGTH OF PIN.
8. 0.00076 MIN GOLD PLATE IN THE LOCALIZED GOLD PLATE AREA, 0.00381 MIN MATTE TIN IN THE LOCALIZED TIN PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.



RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57 THICK P.C. BOARD

2.070	.0815	12.70	.500
1.57	.062	9.86	.388
1.40	.055	9.80	.386
1.00	.039	7.34	.289
0.76	.030	6.86	.270
0.25	.010	6.10	.240
0.13	.005	5.99	.236
0.08	.003	5.33	.210
0.05	.002	5.08	.200
0.00381	0.000150	4.14	.163
0.00127	0.000050	3.86	.152
0.00076	0.000030	3.68	.145
MM	IN	MM	IN

CONVERSION TABLE

BRASS	8	NYLON, UL94V-0	WHITE	1-770968-1
BRASS	7	NYLON, UL94V-0	WHITE	1-770968-0
BRASS	6	NYLON, UL94V-0	WHITE	770968-2
BRASS	5	NYLON, UL94V-0	WHITE	770968-1
MATERIAL	FINISH	MATERIAL	COLOR	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DMN	S. CARPENTER	24JUL03
CHK	C. JONES	24JUL03
APVD	C. JONES	24JUL03

NAME: **STE** TE Connectivity

PRODUCT SPEC: HEADER ASSEMBLY, RIGHT ANGLE, WITH SHORT PEG, 4 CIRCUIT, MINI UNIVERSAL MATE-N-LOK(TM)

APPLICATION SPEC: ---

SIZE: A1 CASE CODE: 00779 DRAWING NO: 770968 RESTRICTED TO: ---

WEIGHT: ---

CUSTOMER DRAWING SCALE: 5:1 SHEET: 1 OF 1 REV: H