

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2015

© COPYRIGHT 2015 BY - TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC - -

DIST - -

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
NC		NEW RELEASE PER E.O. PI9754	18MAR2008	-	RDR
A		REVISED PER ECO-15-001798	19MAR2015	VNB	DM
AI		REVISED PER PCN E-20-000705	28JAN2020	PK	DM
B		REVISED PER PCN-24-219560	30AUG2024	CO	CB

Ø 1.750 ± 0.010
[44.45 ± 0.25]
MAIN POLARIZING KEYWAY

(2.685)
[68.2]
1.030
[26.16]
.505
[12.83]
.100
[2.54]
Ø 1.329
[33.76]
Ø 1.480
[37.59]
1.500-18UNEF-2A
1.1875-18UNEF-2A

1.625
[41.28]

HD34-18-XXP/SX-L005 19M0517

7

DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.
YEAR: FIRST AND SECOND DIGITS. (14=2014)
MONTH: THIRD DIGIT, EXCLUDING I. A=JAN., B=FEB., C=MARCH... (K=OCT.)
DAY: FOURTH AND FIFTH DIGITS (14=14th DAY)
HOUR: SIXTH AND SEVENTH DIGITS (11=11AM)

6

MATERIAL:
RECEPTACLE HOUSING: 6061-T6 ALUMINIUM ALLOY,
RETAINER RING: PA66 GF10 (BLACK),
GROMMET: SILICONE VMQ (GREEN, BLUE, GRAY).

5. RECOMMENDED PANEL THICKNESS: .062 [1.58] TO .1875 [4.76].
4. FOR ARRANGEMENT OF CONTACT LOCATION SEE ENVELOPE DWG 0425-013-1800.
3. THIS CONNECTOR MATES WITH PART NO. HD36-18-XXS/PX-XXXX.
XX= NUMBER OF CAVITIES, X= TYPE OF SEAL,
XXXX= ALL MODIFICATION.
2. 14 PIN ARRANGEMENT SHOWN FOR REF. ONLY.
1. CONSULT FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATIONS.

NOTES:

Ø 1.507 ± 0.005
[38.28 ± 0.12]
1.442^{+0.010}
-0.000
[36.63^{+0.25}
-0.00]

RECOMMENDED PANEL
MOUNTING HOLE

3D VIEW

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 04FEB2008

I. GRANTCHAROVA

CHK 18MAR2008

R. MCCORD

APVD 26FEB2008

S. BEARD

PRODUCT SPEC

108-151014

APPLICATION SPEC

114-151014

WEIGHT

74g

DIMENSIONS:
INCHES [mm]TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±.010 [±.254]
4 PLC	±-
ANGLES	±0° 30' 0"

MATERIAL

FINISH

-

NAME

RECEPTACLE CONNECTOR SIZE 18
BAYONET COUPLING
-L005 MOD

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

-

HD34-18-XXP/SX-L005

-

Customer Drawing

SCALE NONE

SHEET 1 OF 1

REV B

1470-19 (3/11)