



## **VS809-11**

### **VS Series–Level Sensor**

#### **Features**

- ◆ High or low level sensing
- ◆ Internal fitting
- ◆ Reed switch reliability
- ◆ Silicone sealing washer
- ◆ Easy installation

#### **Comments**

- ◆ Normally open or normally closed by float inversion
- ◆ Suitable for a wide range of liquids
- ◆ Interface option available
- ◆ Polypropylene Material

#### **Applications**

- ◆ Continuous 80
- ◆ Water high or low Level
- ◆ Condensate level alarm
- ◆ Drinking water level
- ◆ Cooling systems

## VS809-11N

VS Series—Level Sensor

### Material

<b>Housing/Shuttle Material</b>	Glass Filled Polypropylene
<b>Float Material</b>	Glass Filled Polypropylene
<b>Contact Material</b>	Ruthenium
<b>Float SG</b>	0.68
<b>Operating Temperature °C Medium</b>	-30 to 105 Water
<b>Housing and Float Color</b>	Charcoal

### Mechanical Specifications

<b>Shock</b>	50g for 11mS duration
<b>Vibration</b>	35g up to 500Hz
<b>Maximum Pressure</b>	4.7 Bar
<b>Float Diameter</b>	22mm
<b>IP</b>	IP65

### Switching

<b>Switch Action (Reed Switch)</b>	SPST
<b>Max Switching Voltage VDC</b>	200
<b>Max Switching Voltage VAC</b>	250
<b>Max Switching Current Amps</b>	1
<b>Max Switching Load Watt</b>	70
<b>Operate Mode</b>	N/C with float at bottom stop
<b>Contact Form</b>	A


### Cable

<b>Cable Length</b>	2 x 0.5M single insulated
<b>Connection Type</b>	Stripped Cables
<b>Cable Type</b>	22 AWG 16/0.2mm PVC insulated
<b>Cable Color</b>	Black

### Mounting

<b>Thread</b>	M16
<b>Fitment</b>	Internal
<b>Mounting</b>	Vertical

### Technical Drawing



### NORTH AMERICA

Measurement Specialties, Inc.,  
a TE Connectivity Company  
Phone +1-800-522-6752  
Email: [customercare.hmpt@te.com](mailto:customercare.hmpt@te.com)

### EUROPE

MEAS Deutschland GmbH(Europe)  
a TE Connectivity Company  
Phone: +49-800-440-5100  
Email: [customercare.tlse@te.com](mailto:customercare.tlse@te.com)

### ASIA

Measurement Specialties (China), Ltd.,  
a TE Connectivity Company  
Phone: +86-0400-820-6015  
Email: [customercare.shzn@te.com](mailto:customercare.shzn@te.com)

### TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.