



# **EVS312-21N**

EVS Series • Top or Bottom • Level Sensor

## **Features**

- ◆ Internal fitting
- ◆ Suitable for a wide range of Chemicals
- ◆ Repeatability of operation
- ◆ Reed switch reliability

### Comments

- ◆ Stem length 223.5mm
- ◆ Two Position Level Switching
- ◆ High and Low Level Switch Points
- ◆ Nylon stem and float
- ◆ M16 Fitting

# **Applications**

- ◆ Fuel low level
- ◆ Diesel Fuel
- ◆ Low Oil Detection
- ◆ Alcohols
- ◆ Organic Solvents


Material		Cable	
Housing Material Float Material	Nylon 6.6 Glass filled Nylon 6.6	Cable Length Connection Type	3 x 0.5M single insulated Stripped Cables 18AWG, 16/0.025mm PVC insulated Yellow/Blue/Black
Contact Material	Ruthenium	Cable Type	
Float SG Operating Temperature °C Medium Housing Colour Float Colour	0.74 -30 to 110 Fuel/Oil Blue Blue	Cable Colour	
<b>Mechanical Specifications</b>		Mounting	
Shock	50g for 11mS duration	Thread	M16
Vibration Maximum Pressure	35g up to 500Hz 4.7 Bar	Fitment	External
Float Diameter	4.7 Bar 22mm	Mounting	Vertical
IP	IP65		
Switching		Technical Drawing	
Switching		roommoar Brawing	

Max Switching Voltage VDC Max Switching Voltage VAC 125

**Max Switching Current Amps** 0.4A DC/0.28A AC

Max Switching Load Watt

Both switches normally **Operate Mode** closed at bottom stop **Contact Form** A + B



#### **NORTH AMERICA**

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: customercare.hmpt@te.com

#### **EUROPE**

MEAS Deutschland GmbH(Europe) a TE Connectivity Company Phone: +49-800-440-5100 Email: <u>customercare.tlse@te.com</u>

Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: customercare.shzn@te.com

#### TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.