



# LS509-31 LS Series-Level Sensor

## Features

- ◆ High or low level sensing
- ◆ External fitting
- ◆ Reed Switch reliability
- ◆ Easy installation

## Comments

- ◆ High or low level sensing, single pole double throw
- ◆ Normally open or normally closed by rotating through 180
- ◆ Suitable for a wide range of liquids
- ◆ Interface option available
- ◆ PPS Material

# **Applications**

- ◆ Coolant level indication
- ◆ Water high or low Level
- ◆ Boiler heating element protection
- ◆ Drinking water level
- ◆ Boiling Water

### **Material**

Housing Material Glass Filled PPS
Float Material Glass Filled PPS
Contact Material Ruthenium
Float SG 0.7

loat SG 0.7

Operating Temperature °C -30 to 110

Medium -30 to 110

Boiling, Drinking (Potable) Water

Housing and Float Color Black

### Cable

**Cable Length** 2.5 x 0.5M single insulated **Connection Type** Stripped Cables

Cable Type 18AWG, 32/0.2mm PVC insulated

Cable Color Black

# **Mechanical Specifications**

Shock50g for 11mS durationVibration35g up to 500HzMaximum Pressure2.0 Bar

IP IP65

### Mounting

Thread ½" NPT
Fitment External
Mounting Horizontal

# **Switching**

Switch Action (Reed Switch)

Max Switching Voltage VDC

Max Switching Voltage VAC

Max Switching Current Amps

Max Switching Load Watt

TO

The state of the switch of the

Operate Mode N/C with float horizontal Contact Form A

# **Technical Drawing**

# Mounting Bush Fitting RELEASE ANGLE 40° MAX OPERATE ANGLE 5° MN 102.87 14.051 102.87 14.051 NPT. 14 RIGHT MAND THREAD

### **NORTH AMERICA**

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: customercare.hmpt@te.com

### **EUROPE**

MEAS Deutschland GmbH(Europe) a TE Connectivity Company Phone: +49-800-440-5100 Email: customercare.tlse@te.com

### **ASIA**

Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: customercare.shzn@te.com

# TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.