

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	26Feb2015	GY	CW

2XM6 NUT

4XØ6.5

4XM3 THREAD

58  
39  
32  
27  
77  
103  
146.2  
166

52.2

NOTES:

1. TECHNICAL CHARACTERISTICS:  
 HOUSING MATERIAL: DIE CAST ALUMINIUM ALLOY  
 SURFACE TREATMENT: SEE TABLE  
 OPERATION TEMPERATURE: -40°C~+125°C  
 DEGREE OF PROTECTION: IP68 (MATED)

注释

1. 技术参数:


壳体材料: 铝合金  
 表面处理: 见表格  
 工作温度: -40°C~+125°C  
 防护等级: IP68 (配合)

120.1  
29  
20

103  
82  
35  
32

Panel Cut Out

T1930162000-000	POWDER COATED GRAY RAL7037	H16BPR-AG
T1930161000-000	POWDER COATED SILVERGRAY RAL 7001	H16BPR-AG
T1930160000-000	POWDER COATED BLACK RAL9005	H16BPR-AG
PART NUMBER	SURFACE TREATMENT	DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Gino.Yao 13Dec2014	 TE Connectivity			
DIMENSIONS: mm		CHK Chris.Wang 13Dec2014			NAME H16BPR-AG	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Xiang.Xu 13Dec2014				
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±		PRODUCT SPEC 108-137014				
MATERIAL		APPLICATION SPEC 114-137014	SIZE A3	CAGE CODE -	DRAWING NO C-T193016X000000	RESTRICTED TO -
FINISH		WEIGHT -	SCALE 1:1		SHEET 1 OF 1	REV A
-		Customer Drawing				

1470-19 (3/13)