

File E28476
Project 13ME03525

April 12, 2013

REPORT

on

COMPONENT - Connectors for Use in Data, Signal, Control and Power
Applications

Tyco Electronics Corp
Harrisburg, PA 17111

Copyright © 2013 UL LLC

UL LLC authorizes the above named company to reproduce this Report only for purposes as described in the Conclusion. The Report should be reproduced in its entirety; however to protect confidential product information, the Construction Details Descriptive pages may be excluded.

DESCRIPTION

PRODUCT COVERED:

USR, Component Connector - 0.5 mm Fine Stacking BTB, 24 POS 4mm Height, Emboss, With Cap Hermaphroditic Type Connector.

USR, Component Connector - 0.5 mm Fine Stacking BTB, 24 POS 4mm Height, With Cap Hermaphroditic Type Connector.

USR, Component Connector - 0.5 mm Fine stacking BTB, 30 POS 4mm Height, With Cap Hermaphroditic Type Connector.

GENERAL:

These devices are multi-pole connectors intended for factory assembly where the acceptability of combinations is determined by UL LLC. The devices are identified as follows:

USR indicates investigation to United States Standards, UL 1977.

RATINGS:

Not assigned

Disconnecting Use - Optional, see Sec Gen for required marking.

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC.

Conditions of Acceptability - The following are among the considerations to be made when evaluating the device in the end-use product.

Interruption of Current

1. These devices are not suitable for interrupting the flow of current by connecting or disconnecting the mating connector.

Current-Carrying Capability and Current Ratings

2. These devices have not been subjected to the Temperature test and as a result do not have an assigned current rating. The device's current carrying capability is to be reviewed in the end-use by measuring temperatures on the connector housing and/or terminals when current is flowing through the connector under conditions of normal use.

Insulating Materials

3. These devices employ insulating materials with properties as tabulated below at the minimum thickness employed in the connector housing, the suitability of the insulating materials based on the documented values shall be determined in the end-use application. Please note the values specified in the table when multiple materials are indicated represent the minimum values for the group of materials.

Cat. No.	Insulating Material (#)	Measured Minimum Thickness	Flame Class	HWI	HAI	RTI Elec	Max Operating Temp, °C
*0.5 mm Fine Stacking BTB, 24 POS 4mm Height, Emboss, With Cap Hermaphroditic Type Connector	A for Housing	0.3mm	-	-	-	130	125
	B for Pick Up Cap	1.0mm	V-0	3	0	240	

Cat. No.	Insulating Material (#)	Measured Minimum Thickness	Flame Class	HWI	HAI	RTI Elec	Max Operating Temp, °C
0.5 mm Fine Stacking BTB, 24 POS 4mm Height, With Cap Hermaphro ditic Type Connector	A for Housing	0.2mm	-	-	-	130	125
	B for Pick Up Cap	0.25mm	V-0	3	0	130	
0.5mm Fine stacking BTB, 30 POS 4 mm Height, Tape & Reel, With CAP Hermaphro ditic Type Connector	A for Housing	0.2mm	-	-	-	130	125
	B for Pick Up Cap	0.25mm	V-0	3	0	130	

(#) - Code for Insulating Body Material.

- * A. Tyco Raw Material (R/M) PN 704949
1. Dielectric strength (kV/mm): -
2. CTI: -
- B. Tyco Raw Material (R/M) PN 704105-5
1. Dielectric strength (kV/mm): 34
2. CTI: 3

Miscellaneous

4. The enclosure of the device has live parts that may be exposed to user contact when the connector is energized. The device is suitable for use only within an acceptable enclosure.