File E28476 Vol. 23 Sec. 55 Page 1 Issued: 9-10-97 \*Vol. 53 Sec. 3 Revised: 11-21-01 and Report

DESCRIPTION

PRODUCT COVERED:

USR, CNR - Amp SO DIMM Socket Series and M III Socket Connectors.

## GENERAL:

These devices are multi-pole edgecard connectors employing terminals intended for soldering to a printed wiring board.

USR- Indicates investigation to United States Standard, UL 1977, First Education.

CNR- Indicates investigation to Canadian National Standard, C22.2 No. 182.3 - M1987.

ELECTRICAL RATING:

USR- N/A CNR- < 1 A, < 30 V

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

- 1. These devices should be used only where they will not interrupt the current.
  - 2. These devices have not been tested for current-carrying capability.
- 3. The suitability of the min 0.8 mm (0.031 in) spacings between live parts of opposite polarity (including adjacent poles) and between live parts and exposed dead metal parts shall be determined in the end-use. Dielectric testing has not been performed.
- 4. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.
- 5. The electrical and mechanical between the connector and the printed wiring is to be judged in the end use equipment.
- $\,$  6. The suitability of the mounting means shall be determined in the end use.
- 7. The suitability of the insulating materials used in the molded bodies shall be judged in the end-use equipment.
- 8. The operating temperature of these devices should not exceed the temperature ratings of the insulating materials. These materials may be used interchangeably at a maximum temperature of  $105^{\circ}\text{C}$ .