


DO NOT SCALE

DIMENSIONS IN mm

METRIC


THIRD ANGLE

PROJECTION



NOTES:

- 1 FOR USE ON MINIATURE APPLICATORS (LEFT-RIGHT FEED)
2 PH. BRONZE ELONGATION A50 ≥ 20%.
3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



3 OBSOLETE

1	PRE-TINPLATED	BRASS	160859-8
1	PRE-TINPLATED	Ph BRONZE	160859-7
1	UNPLATED	Ph BRONZE	160859-6
1	SILVERPLATED	Ph BRONZE	160859-5
1	TINPLATED	Ph BRONZE	160859-4
1	UNPLATED	Ph BRONZE	160859-3
1	TINPLATED	BRASS	160859-2
1	UNPLATED	BRASS	160859-1
PLATING	PLATING	MATERIAL	PARTNUMBER

CUSTOMER DRAWING FOR REFERENCE ONLY
WILL NOT BE UPDATED

General : 1 DEC PLC: +/- 0,25
Tolerance : 2 DEC PLC: +/- 0,25

THIS DRAWING IS UNPUBLISHED
RELEASED FOR PUBLICATION - ,19 -

TE TE Connectivity

NAME FASTIN-FASTON® Connector,
.250" sr. TAB CONTACT.

G5	REVISED PER ECN-23-197335	WLS	BHC	07FEB2023
G4	REVISED PER ECN-22-189558	WLS	BHC	09DEC2022
G3	REVISED PER ECO-11-005140	RK	HMR	31MAR11
LTR.	REVISION RECORD	DR.	CHK.	DATE
DR.: J.v.LIEMPT.	CHK.: A.BIJNEN.	APP.: L.v.SOEST.	DWS.No.	
DATE: 23 MAR 1992	DATE: -	DATE: -	C-160859	REV.LTR. G5

SHEET
1 OF 1

A3