

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT 2024 TYCO ELECTRONICS JAPAN G.K. ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		RELEASED	18APR2008	S.K S.M
B		REVISED	06AUG2008	S.K S.M
BI		REVISED ECR-24-201275	13FEB2024	KF TK

△. MATERIAL: 15% GLASS FILLED THERMOPLASTIC
 COLOR: BLACK

△. MATERIAL: 15% GLASS FILLED THERMOPLASTIC
 COLOR: RED

3. MATERIAL OF SEAL: SILICONE RUBBER

△. DIODE: SEE TABLE

△. CATHODE SIDE OF DIODE: CIRCUIT No.1

△ 品名: S3V60、メーカー: 新電元工業(株)			
最大定格		順方向特性	逆方向特性
V _{RM} (V)	I _F (A)	V _F MAX (V)	I _R MAX (μ)
600	3.5	1.05	10

S3V60	AXIAL DIODE	2040104-2
△ DIODE PART NAME	DIODE	PART No.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. KUBOTA 18APR2008	TE Connectivity	
DIMENSIONS: mm		CHK T. KUDO 18APR2008		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S. MANABE 18APR2008	NAME CAP ASSY AMPSEAL16 2P CAP WITH DIODE	
0-PLC ±0.3		PRODUCT SPEC	SIZE A2	
1-PLC ±0.5		APPLICATION SPEC	CAGE CODE 00779	DRAWING NO. C-2040104
2-PLC ±0.13		WEIGHT	RESTRICTED TO	
3-PLC ±0.013		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 OF 1
4-PLC ±0.0001			REV BI	
ANGLES ±				
FINISH				
MATERIAL SEE NOTE				
SEE NOTE				

1471-9 (3/13)