




LOC		DIST		REVISIONS			
AD	00	P	LTN	DESCRIPTION	DATE	DWN	APVD
		A		CREATED BY AUTOMATION PROGRAM	08JUN2011	RKC	JE





NOTCH DESIGNATES ROW A



- 1. MATERIAL:
HOUSING: LCP, GLASS FILLED, UL94V-0.
TERMINALS: HIGH PERFORMANCE COPPER ALLOY.
- 2. FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN ON PCB TAILS, NICKEL OVERALL.
- 3. FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN-LEAD ON PCB TAILS, NICKEL OVERALL.
- 4. SCREWS PACKAGED IN END OF PACKAGING TUBE.
- 5. FOR GROUNDED GUIDE PIN USE Ø3.56±0.08 PTH, Ø3.66 DRILL, AND Ø6.5 PAD.
- 6. KEYING PIN SHOWN IN POSITION A, SEE KEYING CHART ON SHEET 2 FOR OTHER POSITIONS.



LEFT GUIDED BACKPLANE HOLE PATTERN (CONNECTOR SIDE)



SECTION A-A


1.4 TAIL LENGTH
 1.00 MINIMUM BOARD THICKNESS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	07JUN2011	STE TE Connectivity
DIMENSIONS:		CHK	J. EARY 07JUN2011	
mm	0 PLC ±0.25 1 PLC ±0.13 2 PLC ±0.13 3 PLC ±0.13 4 PLC ±0.13	APVD	J. EARY 07JUN2011	NAME IMPACT, 6 PAIR, 8 COLUMN, HEADER LEFT GUIDED, OPEN END WALL SIGNAL MODULE, 0.39 PTH
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		
MATERIAL		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO
FINISH SEE TABLE		WEIGHT		A100779C=2057785
		Customer Drawing	SCALE 5:1	SHEET 1 OF 2 REV A

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
AD	00	P	LTN	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1		-	-

3	H	5.5	8-2057785-6
3	H	4.9	8-2057785-5
3	H	4.5	8-2057785-4
2	H	5.5	8-2057785-3
2	H	4.9	8-2057785-2
2	H	4.5	8-2057785-1
3	G	5.5	7-2057785-6
3	G	4.9	7-2057785-5
3	G	4.5	7-2057785-4
2	G	5.5	7-2057785-3
2	G	4.9	7-2057785-2
2	G	4.5	7-2057785-1
3	F	5.5	6-2057785-6
3	F	4.9	6-2057785-5
3	F	4.5	6-2057785-4
2	F	5.5	6-2057785-3
2	F	4.9	6-2057785-2
2	F	4.5	6-2057785-1
3	E	5.5	5-2057785-6
3	E	4.9	5-2057785-5
3	E	4.5	5-2057785-4
2	E	5.5	5-2057785-3
2	E	4.9	5-2057785-2
2	E	4.5	5-2057785-1
3	D	5.5	4-2057785-6
3	D	4.9	4-2057785-5
3	D	4.5	4-2057785-4
2	D	5.5	4-2057785-3
2	D	4.9	4-2057785-2
2	D	4.5	4-2057785-1
3	C	5.5	3-2057785-6
3	C	4.9	3-2057785-5
3	C	4.5	3-2057785-4
2	C	5.5	3-2057785-3
2	C	4.9	3-2057785-2
2	C	4.5	3-2057785-1
3	B	5.5	2-2057785-6
3	B	4.9	2-2057785-5
3	B	4.5	2-2057785-4
2	B	5.5	2-2057785-3
2	B	4.9	2-2057785-2
2	B	4.5	2-2057785-1
3	A	5.5	1-2057785-6
3	A	4.9	1-2057785-5
3	A	4.5	1-2057785-4
2	A	5.5	1-2057785-3
2	A	4.9	1-2057785-2
2	A	4.5	1-2057785-1
3	-	5.5	2057785-6
3	-	4.9	2057785-5
3	-	4.5	2057785-4
2	-	5.5	2057785-3
2	-	4.9	2057785-2
2	-	4.5	2057785-1
FINISH	KEY POSITION	DIM M	PART NUMBER



REFER TO WWW.TE.COM
FOR PRODUCT AVAILABILITY

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN - 07JUN2011	TE Connectivity
DIMENSIONS: mm		CHK J. EARY 07JUN2011	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. EARY 07JUN2011	NAME: IMPACT, 6 PAIR, 8 COLUMN, HEADER LEFT GUIDED, OPEN END WALL SIGNAL MODULE, 0.39 PTH
0 PLC ±0.25		PRODUCT SPEC	
1 PLC ±0.13		APPLICATION SPEC	SIZE: CAGE CODE DRAWING NO. RESTRICTED TO
2 PLC ±		WEIGHT	A100779C=2057785
3 PLC ±		Customer Drawing	SCALE 5:1 SHEET 2 OF 2 REV A
4 PLC ±			
ANGLES			
FINISH SEE TABLE			