





THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20  
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
	D	RELEASED	6-27-12	CT	DM		
			25OCT2011	KG	DM		



CONTACT TE CONNECTIVITY FOR STANDARD HARDWARE FOR CONNECTOR ATTACHMENT

SHELL  
 ELECTROLESS NICKEL PLATED PER AMS-C-26074 CLASS 1  
 ALUMINUM ALLOY 6061-T6 PER ASTM B221  
 CONTACT RETENTION CLIP QTY = 2 (ASSEMBLED INSIDE SHELL)  
 STAINLESS STEEL PER UNS S30200 PER ASTM A666  
 PLATED SILVER .000400 MIN THICK PER ASTM B700 OVER WOODS  
 NICKEL STRIKE PER ASTM B254

2157449-1  
 PART NUMBER

- 1 CONNECTOR KIT INCLUDES QUADRAx CONTACTS (TE CONNECTIVITY PART# 1445693-3, QTY 2) FOR 100Ω CABLE. NOT INSTALLED
- 2 CONNECTOR IS MARKED WITH TE, TE CONNECTIVITY PART NUMBER & DATE CODE.
- 3 RECESSED CIRCUIT IDENTIFICATION.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. GLATFELTER 24FEB2011	TE Connectivity	
DIMENSIONS: INCHES		CHK D. MILLER 24FEB2011		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. MILLER 24FEB2011	NAME QUADRAx 202 ASSY, PLUG, D-SUB, SIZE 2	
0 PLC ±-		PRODUCT SPEC	SIZE	
1 PLC ±-		APPLICATION SPEC	CAGE CODE	
2 PLC ±.01		WEIGHT	DRAWING NO	
3 PLC ±.005		CUSTOMER DRAWING	RESTRICTED TO	
4 PLC ±-		SCALE 2:1	SHEET 1 OF 1	
ANGLES ±-			REV D	
FINISH				