

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY TYCO ELECTRONICS CORPORATION

ALL RIGHTS RESERVED.

LOC DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A6		RELEASE PER ECR-19-009634	15JUL2019	LZ	TD
C		REVISED PER ECR-20-100866	26NOV2020	BDA	DL

NOTE:

- CONTINUOUS STRIP ON REELS
- MATING TAB ACCORDING TO UL310 AND IEC61210 NORM. (WIDTH\*THICKNESS IS 6.3\*0.8mm)
- WIRE SIZE IS #20-#18 AWG(0.5-1.0 sqmm)
- INSULATION RANGE IS  $\varnothing$ 1.8-2.5mm
- CUT-OFF TAB LENGTH IS 0.5MM MAX.
- $\triangle$  PRELIMINARY, NOT FOR PRODUCTION.
- APPLICATION FEED LENGTH 21.4mm.

SECTION E-E

SECTION B-B

Pre-TIN	CuNiSi	$\triangle$ 2178299-3
Pre-TIN	BRASS	$\triangle$ 2178299-2
Pre-NICKEL	Steel	2178299-1
FINISH	MATERIAL	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN VIBHUTHI 19NOV2012

CHK SUBHASH M 19NOV2012

APVD SURESH T N 19NOV2012

PRODUCT SPEC 108-64027

APPLICATION SPEC 114-64027

WEIGHT -

Customer Drawing

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	$\pm 0.5$
1 PLC	$\pm 0.5$
2 PLC	$\pm 0.1$
3 PLC	$\pm$
4 PLC	$\pm$
ANGLES	$\pm 1^\circ$

MATERIAL SEE TABLE

FINISH SEE TABLE

TE Connectivity

NAME

6.3 SRS F-SPRING LIF RECEPTACLE

SIZE

A3

CAGE CODE

00779

DRAWING NO

C=2178299

RESTRICTED TO

-

SCALE 4:1

SHEET 1 OF 1

REV C

1470-19 (3/11)