

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECR-18-002379	27FEB2018	BW	MD
	A2	REVISED PER ECO-18-009651	19JUN2018	BKW	MD
	A3	REVISED PER ECR-20-100299	10AUG2020	BDA	WW
	A4	ECR-23-187950	26SEP2023	SP	FL

NOTES:

- CONTINUOUS STRIP ON REELS
- REFERENCE CRIMP INFORMATION:
WIRE RANGE - 22 TO 18AWG
INSULATION RANGE - 1.5 TO 2.8MM,
WIRE BARREL - .080 INCH CRIMP WIDTH, F TYPE
INSULATION BARREL - .130 INCH CRIMP WIDTH, F TYPE
- RECOMMENDED MATING TAB:
TAB WIDTH 6.3 ± 0.1 MM, THICKNESS 0.8 ± 0.03 MM
HOLE DIAMETER 1.7MM, CENTER LOCATED 2.5MM FROM TIP

△ 4 DIFFERENT MARKING PART NUMBER

SECTION F - F

SECTION J - J

SECTION G - G
SCALE 8:1

SECTION H - H
SCALE 8:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL
BRASSTOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±1.00
1 PLC ±0.50
2 PLC ±0.25
3 PLC ±
4 PLC ±
ANGLES ±FINISH
SEE TABLE

DWN 06DEC2016

CHK J. POTERJOY

F. LUPO 06DEC2016

APVD R. ROBONE 06DEC2016

PRODUCT SPEC

108-143029

APPLICATION SPEC

114-2074

WEIGHT -

CUSTOMER DRAWING

TIN	BRASS	2238136-4 △ 4
TIN	BRASS	2238136-2
PLAIN BRASS	BRASS	2238136-1
FINISH	MATERIAL	PART NO

NAME
RECEPTACLE, POSITIVE-LOCK,
RAST 6.35 SERIES

SIZE A3 CAGE CODE - DRAWING NO C-2238136 RESTRICTED TO -

SCALE 5:1 SHEET 1 OF 1 REV A4

1470-19 (3/13)