



P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	REVISED (ECR-24-214763)	15JUL2024	SW	YH
	B	REVISED (ECR-25-238124)	14MAR2025	SW	YH
	C	REVISED (ECR-25-239568)	28MAR2025	SW	YH
	C1	REVISED (ECR-25-240350)	03APR2025	SW	YH

ISO VIEW (SCALE 1:1)

2365978-2 / 1-2365978-1 2-2365978-3 / 3-2365978-6



CODE	CODE A	CODE B
P/N	2365978-2/2-2365978-3	1-2365978-1/3-2365978-6
SHAPE		

KEY CODE TABLE

NOTE

1. GENERAL TOLERANCE : ± 0.3 , $\pm 3^\circ$
2. DELEVRY CONDITION : DBL IN 1st LOCKING POSITION
3. APPLICABLE RECEPTACLE CONTACT P/N : SEE TABLE I
4. THE MATING HEADER ASS'Y P/N : X-2365882-X
5. ONLY APPLY FOR 2-2365978-X / 3-2365978-X

NO.	COLOR	MATERIAL	DESCRIPTION	Q'TY
2	BLACK	PBT	025 36P PLUG DBL(B)	-
	YELLOW	PBT	025 36P PLUG DBL	-
1	RED	PBT	025 36P PLUG HSG(B)	-
	GRAY	PBT	025 36P PLUG HSG(A)	-
	NATURAL	PBT	025 36P PLUG HSG(B)	-
	BLACK	PBT	025 36P PLUG HSG(A)	-

TABLE I.

CONTACT	PART NO.	WIRE SIZE (SQ)	INSULATION DIAMETER(mm)	REMARK
.025	2366531-1	0.22	1.0~1.05	5
	2366531-2	0.3~0.5	1.1~1.7	
	5-2366531-1	0.22	1.0~1.05	
	5-2366531-2	0.3~0.5	1.1~1.7	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC $\pm$ 1 PLC $\pm$ 2 PLC $\pm$ 3 PLC $\pm$ 4 PLC $\pm$ ANGLES $\pm$ FINISH -
MATERIAL	SEE TABLE

DWN BH LEE	TE Connectivity			
CHK DG JEONG				
APVD YJ YOUN				
PRODUCT SPEC -				
APPLICATION SPEC -	NAME 025 36P PLUG ASS'Y			
WEIGHT -	SIZE A3	CAGE CODE 00779	DRAWING NO C-2365978	RESTRICTED TO -
CUSTOMER DRAWING	SCALE 1:1	SHEET 1	OF 1	REV C1