


2825-202-0000

REVISIONS

SYM	DESCRIPTION	DATE	APPROVED
N/C	NEW RELEASE PER E.O. 84003	6-20-77	R.H.
A	REVISED PER E.O. 86764	11-1-78	M.K.
B	REVISED PER E.O. 92940	9-30-81	C. Stahl

TABLE I

REF #	PLATING
1	.000050 INCH MINIMUM GOLD PER MIL-G-45204, TYPE II OVER COPPER FLASH
2	.000060 INCH MINIMUM GOLD PER MIL-G-45204, TYPE II OVER .000040 INCH MINIMUM NICKEL PER QQ-N-290



PART NUMBER	A REF	B±.002	C±.007	D ^{+.050} _{-.000}	E ^{+.062} _{-.000}	F ^{+.048} _{-.000}	G ^{+.045} _{-.000}	PLATING (SEE TABLE 1)
101179	.663	.018	.030	N/A	N/A	.008	.041	1
106460	.907	.018	.060	.151	.078	.257	.288	1
106690	.907	.018	.120	.151	.078	.257	.288	1
106393	.776	.018	.201	.021	N/A	.127	.158	1
107890	.928	.018	.353	.173	.100	.279	.312	1
107891	.725	.018	.150	N/A	N/A	.076	.109	1
108437	.838	.029	.180	.082	.009	.188	.221	1
110594	.561	.018	.086	N/A	N/A	.012	.045	1
111798	1.049	.018	.250	.293	.220	.399	.432	1
114067	.756	.018	.181	.001	N/A	.107	.140	1
114068	.975	.018	.400	.220	.147	.326	.359	1

1. SEE "GENERAL DESCRIPTION" IN APPROPRIATE SUBMINIATURE CATALOG SECTION FOR ELECTRICAL SPECIFICATIONS.
2. FOR AVAILABLE CONTACT ARRANGEMENTS REFER TO: 73500 FOR RSM SERIES
74500 FOR RTK SERIES
75500 FOR RE/RM SERIES
3. FOR INSERTION/REMOVAL USE M15570-22-1 TOOL
4. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.

NOTE:

SIGNATURE & DATE	
DR	C Sawyer 6-20-77
CHK	Paul van Haringen
PE	Paul van Haringen
APPD	
SCALE	WT

CONTACT, SOCKET
22 GAGE SUBMINIATURE
REAR INSERTION & REMOVAL
FOR FLAT CABLE

INFORMATION DRAWING

CP	MATL CODE
The Deutsch Company ELECTRONIC COMPONENTS DIVISION Municipal Airport Banning, California	
B	2825-202-0000
PAGE SIZE	CODE 11111 SHEET OF