


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AF	50	P	LTR	DESCRIPTION	DATE	DWN	APVD
		S1		REVISED PER ECO-15-008427	08JUN15	JR	DH



- 1 MATES WITH .032±.001x.250 TAB
- 2 WIRE STRIP LENGTH .281
- 3 INSULATION SIZE .135 MAX DIA
- 4 CONTINUOUS STRIP ON REELS
- 5 DIMENSION DOES NOT INCLUDE TRIM BURR
- 6 .015 MAX CARRIER TRIM BURR PER SIDE IS ALLOWABLE IN THE SHADED AREA

STANDARD	HOUSING:NYLON,COLOR-BLACK TRANSLUCENT RECEPTACLE:BRASS, TIN	9-520183-2
BULK	HOUSING:NYLON,COLOR-RED TRANSLUCENT RECEPTACLE:BRASS, TIN	5-520183-2
STANDARD	HOUSING:NYLON,COLOR-RED TRANSLUCENT RECEPTACLE:#3 HARD PH BRONZE, TIN	2-520183-4
	HOUSING:NYLON,COLOR-RED TRANSLUCENT RECEPTACLE:BRASS, TIN	2-520183-2
PACKAGING	MATERIAL & FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN P FORTNEY 10/18/88	STE TE Connectivity
		CHK JR RUTH 10/18/88	
		APVD K RANDOLPH 10/21/88	
		NAME RECEPTACLE ASSY,ULTRA-FAST, .250 SERIES,22-18 AWG	
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PRODUCT SPEC 108-2043	RESTRICTED TO
	0 PLC ± -	APPLICATION SPEC 114-2123	
	1 PLC ± -	WEIGHT -	SIZE A3
	2 PLC ± -	CUSTOMER DRAWING	CAGE CODE 00779
	3 PLC ± .015	SCALE 4:1	DRAWING NO C-520183
	4 PLC ± -	SHEET 1 OF 1	REV S1
	ANGLES ± -		
MATERIAL SEE TABLE	FINISH SEE TABLE		