SPECIFICATION CONTROL DRAWING					SCD 55A0831	
Title THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED,					Date	Revision
	GENERAL PURPOSE, 600 VOLT This specification sheet forms a part of the latest issue of Raychem				1-13-17	D
СОМ	PONENT WIRES - 55A0811					
		CABLE CONST	RUCTION DE	TAILS		
	PART NUMBER <u>1</u> /	CONDUCTOR SIZE (AWG)	R OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)	
	55A0831-26-*	26	.086	.091	5.2	
	55A0831-24-*	24	.097	.102	7.0	
	55A0831-22-*	22	.108	.112	9.8	
	55A0831-20-*	20	.125	.130	14.4	
	55A0831-18-*	18	.151	.158	22.0	
	55A0831-16-*	16	.166	.173	27.5	
	55A0831-14-*	14	.203	.210	42.2	
	55A0831-12-*	12	.240	.246	62.7	
	55A0831-10-*	10	.289	.298	99.1	
	55A0831-8-*	8	.421	.438	185.	
	55A0831-6-*	6	.521	.542	289.	
	55A0831-4-*	4	.670	.691	459.	
CABLE RATINGS AND ADDITIONAL REQUIREMENTS         TEMPERATURE RATING: 150°C         Maximum continuous conductor temperature         VOLTAGE RATING: 600 volts (rms) at sea level         DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz         INSULATION FLAWS:         Spark Test, 5.7 kV (rms) at 3 kHz         Impulse Dielectric Test, 8.0 kV (peak)           // PART NUMBER:           Maximum continuous conductor temperature           // PART NUMBER:           Maximum continuous conductor temperature              Impulse Dielectric Test, 8.0 kV (peak)   // PART NUMBER:              // PART NUMBER:              // PART NUMBER:         The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing.         Example: AWG 22, orange, blue, and white component wires: 55A0831-22-3/6/9						
Tyco Electroni <u>1</u> / COLORS ANI AN ALTERNA	E: Nominal values are for information Users should evaluate the suitabili cs Corporation also reserves the right to make c D COLOR CODE DESIGNATORS SHALL BE IN AC TIVE COLOR CODE MAY REPLACE MIL-STD-681 AY BE ADDED TO THE PART NUMBER, AS NECE	ty of this product for thei hanges in materials or p CORDANCE WITH MIL-S COLOR CODE DESIGNA	r application. Spe rocessing, which TD-681. HOWEVE ATORS. (EXAMPL	ecifications are sub do not affect comp ER, DUE TO LENGT E: "901/902" MAY	liance with any specifica H LIMITATIONS OF THE BE REPLACED BY "Axx	ation, without notification to Buyer. RAYCHEM PART NUMBER, xx".) OTHER CODES AND
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.					Raychem Wire & Cable
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.					501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-522-6752
	REFERENCED DOCUMENTS SHALL BE OF TH					Fax: 1-650-361-6297

© 2009-2017 Tyco Electronics Corporation. All rights reserved.