



SPECIFICATION CONTROL DRAWING				SCD		55A1816	
Title ONE CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, 600 VOLT				Date 08-21-24		Revision B	
This specification sheet forms a part of the latest issue of Raychem Specification 55A.							
<div>COMPONENT WIRES - 55A0816 SHIELD - NICKEL-COATED COPPER JACKET - RADIATION-CROSSLINKED, MODIFIED ETFE</div> 							
CABLE CONSTRUCTION DETAILS							
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (inch)		OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM	
55A1816-26-*	26	38	.006	.008	.073	.079	5.6
55A1816-24-*	24	38	.006	.008	.078	.084	6.6
55A1816-22-*	22	38	.006	.008	.083	.089	7.9
55A1816-20-*	20	38	.006	.008	.091	.098	10.0
55A1816-18-*	18	38	.006	.008	.103	.111	13.8
55A1816-16-*	16	38	.006	.008	.110	.119	16.1
CABLE RATINGS AND ADDITIONAL REQUIREMENTS							
<p>TEMPERATURE RATING: 200°C Maximum continuous conductor temperature</p> <p>VOLTAGE RATING: 600 volts (rms) at sea level</p> <p>ACCELERATED AGING: 300 ± 3°C for 7 hours</p> <p>BLOCKING: 200 ± 3°C for 6 hours</p> <p>DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz</p> <p>FLAMMABILITY: Procedure 1, 3 seconds (maximum), 3 inches (maximum); no flaming of facial tissue</p> <p>JACKET COLOR: White preferred</p> <p>JACKET ELONGATION AND TENSILE STRENGTH: Elongation, 50% (minimum) Tensile Strength, 5000 lbf/in² (minimum)</p> <p>JACKET FLAWS: Spark Test, 1000 Volts, 60 Hz (rms) Impulse Dielectric Test, 6.0 kV (peak)</p>				<p>LIFE CYCLE: 230 ± 3°C for 500 hours</p> <p>LOW TEMPERATURE-COLD BEND: -65 ± 2°C for 4 hours</p> <p>SHIELD COVERAGE: 85% (minimum)</p> <p>VOLTAGE WITHSTAND: (Post Environmental) 1000 volts (rms), 60 Hz, 1 minute</p>			
				<p>1/ PART NUMBER: The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color. Example: AWG 20, white component wire; white jacket; 55A1816-20-9-9</p>			
<p>NOTE: Nominal values are for information only. Nominal values are not requirements.</p>							
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. TE Connectivity also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.							
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.							
Page 1 of 1	Raychem, TE Connectivity and TE (logo) are trademarks.			 <div>Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-522-6752 Fax: 1-650-361-6297</div>			
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL						
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.						