


All terminals tinned. Tin height from stand-off 0,3mm max. (except for coil terminals, already pre-tinned)

Circuit Diagram (Make contact)



- 1) Stand-off
- 2) Assembly and positioning aid
- 3) Area free of components or pcb tracks
- 4) Length of terminals without tin. With tin max. 5mm.

Pin layout compatible with V23133-A...

PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.				CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD		PAPER SIZE A3	
APPLICABLE SPEC.:				FINISH			
				DIMENSIONS APPLY		PLATING	
				SCALE 2:1		WEIGHT	
				MATERIAL			
				PART NAME			
				Power Relay K Sealed Dimension drawing NO			
				DWG NO.		SHT.	
				C23303-A0076-A022-CD		1	
				OF 1			
REV. CHANGE ORDER		DATE		APP.			

