

REV. B
DCO 300859


TOLERANCES ±.010" - UNLESS OTHERWISE SPECIFIED

COIL: @ 25°C
RESISTANCE _____ CURRENT: .04 A MAX.
NOMINAL VOLTAGE _____ 115 VAC - 400 Hz
MUST OPERATE _____ 70.0 VAC MAX., 400 Hz
MUST RELEASE _____ 25.0 VAC MAX., 8.0 VAC MIN., 400 Hz

ENVIRONMENT:
VIBRATION _____ 10 _____ Hz TO _____ 3000 _____ Hz @ _____ 30 _____ g's
SHOCK _____ 200 _____ g's _____ 6 _____ MS. DURATION
TEMPERATURE _____ -70 _____ °C TO _____ +125 _____ °C

NOTES: OPERATE TIME 20 MS MAX.
RELEASE TIME 50 MS MAX.
CONTACT BOUNCE 1 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: _____
10 AMPS 28 VDC, 115 VAC 400 Hz RESISTIVE
100,000 OPERATIONS

DR. B.D. 16MAY2008 | CK. J.M.B. 5/19/08

Tyco Electronics ©COPYRIGHT 2005
TYCO ELECTRONICS CORPORATION
ALL INTERNATIONAL RIGHTS RESERVED

CUST. _____ CATALOG ITEM _____
CUST. NO. _____ REV. _____

TE NUMBER
1617756-9

CII PART NUMBER
FCA-410-DY8