

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	20OCT2017	RL	CW
	B	ECR-17-017888	14DEC2017	RL	CW

M4 SCREW RECOMMENDED  
TIGHTENING TORQUE 1.2Nm  
M4 螺丝推荐扭力矩为 1.2Nm

16X M3 SCREW, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm  
16X M3 螺丝推荐扭力矩为 0.5Nm

4X M3 SCREW, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm  
4X M3 螺丝推荐扭力矩为 0.5Nm

NOTES:

1. TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250 V  
RATED CURRENT: 16 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4 KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.5-2.5 mm<sup>2</sup> (20-14 AWG)  
CONTACT FINISH: SILVER PLATED  
CONTACT TYPE: SCREW CONTACT

注释:

1. 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 16A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4 KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500 次  
接线范围: 0.5-2.5 mm<sup>2</sup> (18-14 AWG)  
端子表面处理: 镀银  
接线类型: 螺丝连接

PANEL CUT FOR INSERTS FOR USE  
WITHOUT HOODS/ HOUSINGS

不装壳体的面板安装开孔尺寸

4X  $\phi 3.3$

T2010162201-001	HA-016-M	HA-016 FEMALE INSERT, NO LOGO HA-016母插, 无LOGO
PART NUMBER 料号	PART DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 20OCT2017 ROY LIU	 TE Connectivity	NAME HA-016-F										
DIMENSIONS: mm		CHK 20OCT2017 GINO YAO												
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 20OCT2017 CHRIS WANG												
<table border="1"> <tr> <td>0 PLC</td> <td>±-</td> </tr> <tr> <td>1 PLC</td> <td>±-</td> </tr> <tr> <td>2 PLC</td> <td>±-</td> </tr> <tr> <td>3 PLC</td> <td>±-</td> </tr> <tr> <td>4 PLC</td> <td>±-</td> </tr> <tr> <td>ANGLES</td> <td>±-</td> </tr> </table>		0 PLC			±-	1 PLC	±-	2 PLC	±-	3 PLC	±-	4 PLC	±-	ANGLES
0 PLC	±-													
1 PLC	±-													
2 PLC	±-													
3 PLC	±-													
4 PLC	±-													
ANGLES	±-													
MATERIAL	FINISH	APPLICATION SPEC 114-137045	SIZE A3	CAGE CODE 00779	DRAWING NO T2010162201001	RESTRICTED TO								
CUSTOMER DRAWING		WEIGHT	SCALE 1:1		SHEET 1 OF 1	REV B								

1470-19 (3/13)