

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	01APR2015	DW	CW
	B	ECR-15-014907	14OCT2015	DL	CW
	BI	ECR-19-012251	04SEP2019	WQR	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:
 INSULATION MATERIAL: PC
 RATED VOLTAGE: 500V
 RATED CURRENT: 16A
 INSULATION RESISTANCE: $\geq 400M\Omega$
 RATED IMPULSE VOLTAGE: 6KV
 POLLUTION DEGREE: 3
 FLAMMABILITY: UL94V-0
 MATING CYCLES: 500 CYCLES
 WIRE RANGE: 0.14-4 mm² (26-12 AWG)
 CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.
 (ORDER No. REFER TO DRAWING: T20300X20XX000)

注释:

1. 技术参数:
 绝缘材料: PC
 额定电压: 500V
 额定电流: 16A
 绝缘电阻: $\geq 400M\Omega$
 额定脉冲电压: 6KV
 污染等级: 3
 阻燃等级: UL94V-0
 插拔次数: 500次
 接线范围: 0.14-4 mm² (26-12 AWG)
 接线类型: 冷压接

2. 端子需要单独订购。
 (订货号参考图面: T20300X20XX000)


4X M3 THREAD, RECOMMENDED
 TIGHTENING TORQUE 0.5Nm
 4X M3 螺丝, 推荐拧紧力矩0.5N.m

M4 THREAD
 RECOMMENDED
 TIGHTENING TORQUE 1.2Nm
 M4 螺丝, 推荐拧紧力矩1.2N.m

PANEL CUT FOR INSERTS FOR USE
 WITHOUT HOODS/ HOUSINGS

不使用防护外壳时芯件的安装开孔图

T2059462201-000	HEE-046-F	HEE-046 FEMALE INSERT, NO TE LOGO HEE-046母插, 无TE LOGO
PART NUMBER 料号	PART DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 01APR2015 David Wang	 TE Connectivity				
DIMENSIONS: mm		CHK 01APR2015 Chris Wang			NAME HEE-046 FEMALE INSERT, NO TE LOGO		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 01APR2015 Xiang Xu					
0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-		PRODUCT SPEC 108-106137					
MATERIAL		APPLICATION SPEC 114-106137	SIZE A3	CAGE CODE 00779	DRAWING NO C-T2059462201000	RESTRICTED TO -	
		WEIGHT -	SCALE 1:1		SHEET 1	OF 1	REV BI
		Customer Drawing					

1470-19 (3/13)