

M120/35.FF



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products → Low Voltage Products and Systems → Connection Devices → Terminal Blocks → Solution Series

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | M120/35.FF |
| Product ID: | 1SNA115146R1500 |
| EAN: | 3472591151466 |
| Catalog Description: | M120/35.FF |
| Long Description: | - Compact two stud terminal block, - Lug mounting in accordance with NF C 20-130 and DIN 46234, - Various marking options, - Rail or base mounting. |

Ordering

| | |
|--------------------------------|----------|
| Color: | Grey |
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85369010 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SNC160020C0201 |
| Instructions and Manuals: | 1SNC160020C0201 |

Dimensions

| | |
|------------------------------------|-------|
| Product Net Width: | 35 mm |
| Product Net Height: | 69 mm |
| Product Net Depth / Length: | 51 mm |
| Product Net Weight: | 130 g |

Technical

| | |
|---|---|
| Rated Cross-Section: | 70 mm ² |
| Spacing: | 35 mm |
| Connection Type: | Stud |
| Function: | Feed-through |
| Number of Levels: | 1 |
| Connecting Capacity Main Circuit: | Stud / Flexible 1x 2.5 ... 70 mm ² Stud / Rigid 1x 2.5 ... 70 mm ² |
| Rated Current (I_n): | Main Circuit 192 A |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 8000 A |
| Rated Voltage (U_r): | 1000 V |
| Pollution Degree: | 3 |

| | |
|------------------------------|--|
| Insulation Material: | Polyamide |
| Mounting on DIN Rail: | G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Tightening Torque: | Cable Lug 12 N·m |

Technical UL/CSA

| | |
|--|--------------------|
| Maximum Operating Voltage UL/CSA: | Main Circuit 600 V |
| Connecting Capacity UL/CSA: | Stranded 250 AWG |

Environmental

| | |
|---------------------------------|--|
| Ambient Air Temperature: | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| RoHS Status: | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|--|-----------------|
| cUL Certificate: | 1SND165000A0203 |
| Declaration of Conformity - CE: | 1SND225011U1000 |
| EAC Certificate: | 1SND161009A1100 |
| Environmental Information: | 1SND220022E1002 |
| Instructions and Manuals: | 1SNC160020C0201 |
| RoHS Information: | 1SND230022F0204 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code: | X |
| ETIM 4: | EC000897 - Feed-through terminal block |
| ETIM 5: | EC000897 - Feed-through terminal block |
| ETIM 6: | EC000897 - Feed-through terminal block |

Container Information

| | |
|--|---------------|
| Package Level 1 Units: | 10 piece |
| Package Level 1 Width: | 135 mm |
| Package Level 1 Depth / Length: | 175 mm |
| Package Level 1 Height: | 74 mm |
| Package Level 1 Gross Weight: | 1.3 kg |
| Package Level 1 EAN: | 3472591151466 |
| Package Level 2 Units: | 80 piece |
| Package Level 2 Width: | 300 mm |
| Package Level 2 Depth / Length: | 500 mm |
| Package Level 2 Height: | 150 mm |

| | |
|--------------------------------------|------------|
| Package Level 2 Gross Weight: | 21.3 kg |
| Package Level 3 Units: | 3840 piece |
| Product Packing Type: | Box |

