



## B4503

### Omnidirectional Antennas 450-470 MHz

#### FEATURES AND BENEFITS

- 5/8 wave design for true 3-dBi performance
- Easy installation with optional NMO mounts
- Special UV-treated radome – resists sun damage
- 100% tested on a network analyzer


#### ELECTRICAL SPECIFICATIONS

Model Name	B4503
Operating Frequency (MHz)	450-470
VSWR - Max	< 1.5:1
Gain (dBi)	3.0
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	100
Polarization	Vertical
Pattern	Omnidirectional
Elevation Plane 3 dB Beamwidth Port 1	70°
Azimuth Plane 3 dB Beamwidth Port 1	360°

#### MECHANICAL SPECIFICATIONS

Dimensions - H x D - mm (inches)	356.0 x 36.6 (14.0 x 1.44)
Weight - kg (lbs.)	< 0.23 (< 0.5)
Flat Plate Area - square feet	0.023
Cable Type	None
Mounting	NMO mountable
Noise Suppressor	BlackHawk NS 1535 1-35 volt, 15 Amp (sold separately)

## RADIATION PATTERN



**Elevation Pattern (Y, Z or H-plane)**

### TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

### te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

10/21 Original

