

CRSM CT CABLE TAP SPLICES

HEAT-SHRINK WRAPAROUND CABLE TAP SPLICES (1000V)

KEY FEATURES

- Sealant coated
- RUS accepted
- Wraparound

TE Connectivity's (TE) Raychem CRSM CT cable tap splices can be used as a wraparound, sealed cable tap splice. The CRSM CT is sealant coated, and mainly for use on standard poly- or elastomeric insulated conductors.

TE's CRSM CT is RUS accepted for use with compression and split-bolt connectors.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.



CRSM CT Cable Tap Splices







Qualified to ANSI C119.1 rated to ICEA electrical withstand test for 1000 volts.

PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)					
Description	Sleeve Length	Conductor Main (1000V max) (AWG/ kcmil)	Conductor Tap (1000V max) (AWG/ kcmil)	Connector Dimension	Standard Pack
Compression Connector					
CRSM-CT-34/10-150	6 (152)	#8 - #2	#10 - #2	2 (51)	10
CRSM-CT-53/13-200	8 (203)	#2 - 4/0	#10 - 4/0	4 (102)	10
CRSM-CT-84/20-250	10 (254)	4/0 - 500	#2 - 500	6 (152)	10
Standard Split Bolt Connector					
CRSM-CT-53/13-200	8 (203)	#8 - #2	#14 - #2	1.5 (38)	10

Dimension values provided are typical.

ORDERING INFORMATION

- 1. Select the appropriate catalog number based on the main and tap conductor sizes and connector type for electrical repair (1000 volts max.).
- 2. Selections are based on typical dimensions for low-voltage insulated cable Confirm selection with cable dimensions to assure proper sizing.
- 3. Kits do not contain connectors.
- 4. Kits include insulating sleeve, sealant strip, and stainless steel channel closure.
- 5. Standard package: 10 kits/box.

TECHNICAL REPORT

Standard test reports: EDR-5192 UV resistant test reports: EDR-5361

te.com/energy

© 2014, 2016 TE Connectivity Ltd. family of companies. All Rights Reserved. EPP-2806-DDS-6/16-EN-AMS-CRSM-CT-Raychem E562 06/16

Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA: + 1800 327 6996 + 33 380 583 200 France: UK: + 44 0870 870 7500 Germany: + 49 896 089 903 + 34 916 630 400 Spain: + 39 333 250 0915 Italy: + 32 16 351 731 Benelux: Canada: +1(905)475-6222 + 52 (0) 55-1106-0800 Mexico: + 54 (0) 11-4733-2200 Latin/S. America: + 86 (0) 400-820-6015 China:

