



## MECHANICAL SHEAR BOLT CONNECTORS BSL

FOR LOW VOLTAGE APPLICATION UP TO 1.5 kV

### KEY FEATURES

- Wide application range
- Compact design
- Can be used with almost every type of conductor and material
- Torque-controlled shear head bolts\* guarantee an excellent electrical contact
- Easy installation with standard tool
- LV application up to 1.5 kV
- Designed to meet DIN-47640\*\* and IEC-61238-1 class A requirements

TE Connectivity's (TE) shear bolt connectors BSL are designed for use in low voltage applications. Only four sizes cover conductor sizes from 1,5 to 240mm<sup>2</sup>.

Connector bodies are made of a high tensile tin-plated aluminium alloy\*. The internal surfaces of the conductor holes are grooved at the manufacturing stage to provide excellent electrical performance.

Connectors are available with or without oil barrier (as blocked and unblocked types) depending on the application requirements.

All aluminium alloy contact bolts have shear-heads\*, these bolts are treated with a highly lubricating agent. Shear-head bolts are irremovable once their heads have been sheared off except REM connectors.

**Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.**



**SELECTION TABLE FOR BLOCKED TYPE CONNECTORS**

Application range - Conductor type									
Description		Al circular stranded	Al circular solid	Al sector stranded	Al sector solid	Cu circular stranded	Cu circular solid	Cu sector stranded	Cu sector solid
<b>BSLB-4/16* (1)</b>	Cross-sectional range (mm <sup>2</sup> )					1.5 - 16	1.5 - 16		
	Conductor diameter (mm)					1.5 - 5.0	1.5 - 4.6		
<b>BSLB-6/25**</b>	Cross-sectional range (mm <sup>2</sup> )	6 - 25	6 - 25			6 - 25	6 - 25		
	Conductor diameter (mm)	2.8 - 6.5	2.7 - 5.7			2.8 - 6.5	2.7 - 5.7		
<b>BSLB-10/50 (1)</b>	Cross-sectional range (mm <sup>2</sup> )	10 - 50	10 - 50	10 - 50	10 - 50	10 - 50	10 - 50	10 - 50	10 - 50
	Conductor diameter (mm)	4.0 - 9.1	3.5 - 7.8			4.0 - 9.1	3.5 - 7.8		
<b>BSLB-35/95 (1)</b>	Cross-sectional range (mm <sup>2</sup> )	35 - 95	35 - 95	35 - 95	35 - 95	25 - 95	35 - 95	35 - 95	35 - 95
	Conductor diameter (mm)	6.6 - 12	6.1 - 11			5.6 - 12.9	6.1 - 11		
<b>BSLB-35/95-REM (2)</b>	Cross-sectional range (mm <sup>2</sup> )	35 - 95	35 - 95	35 - 95	35 - 95	25 - 95	35 - 95	35 - 95	35 - 95
	Conductor diameter (mm)	6.6 - 12	6.1 - 11			5.6 - 12.9	6.1 - 11		
<b>BSLB-25/150 S-AS (1)</b>	Cross-sectional range (mm <sup>2</sup> )	25 - 95	25 - 95	25 - 150	25 - 150	25 - 95	25 - 95	25 - 150	25 - 150
	Conductor diameter (mm)	5.7 - 12.5	5.5 - 11.0			5.7 - 12.5	5.5 - 11.0		
<b>BSLB-25/150 S-AS-REM (2)</b>	Cross-sectional range (mm <sup>2</sup> )	25 - 95	25 - 95	25 - 150	25 - 150	25 - 95	25 - 95	25 - 150	25 - 150
	Conductor diameter (mm)	5.7 - 12.5	5.5 - 11.0			5.7 - 12.5	5.5 - 11.0		
<b>BSLB-25/150-S-I (3)</b>	Cross-sectional range (mm <sup>2</sup> )	25 - 95	25 - 95	25 - 150	25 - 150	25 - 95	25 - 95	25 - 150	25 - 150
	Conductor diameter (mm)	5.7 - 12.5	5.5 - 11.0			5.7 - 12.5	5.5 - 11.0		
<b>BSLB-95/240 (1)</b>	Cross-sectional range (mm <sup>2</sup> )	95 - 240	95 - 240	95 - 240	95 - 240	70 - 240		95 - 240	
	Conductor diameter (mm)	11.0 - 20.0	10.5 - 18.0			9.3 - 20.0			
<b>BSLB-95/240-REM (2)</b>	Cross-sectional range (mm <sup>2</sup> )	95 - 240	95 - 240	95 - 240	95 - 240	70 - 240		95 - 240	
	Conductor diameter (mm)	11.0 - 20.0	10.5 - 18.0			9.3 - 20.0			

(1) Unblocked version available on this connector size, description starts with BSLU  
 (2) Shear-head bolts removable after installation using an 8mm A/F inner hexagon socket for BSLB-25/150 S-AS-REM and 5mm A/F inner hexagon socket for BSLB-35/95-REM & BSLB-95/240-REM  
 (3) Body insulated (red) according to IEC 60900.

\*BSL-4/16 size with brass connector body and without shear-head bolts  
 \*\* BSLB-6/25 comply with IEC 61238-1 class A but not with DIN 47640

**DIMENSIONS AND CHARACTERISTICS OF CONNECTORS**

Description	Length (mm)	Outer diameter (mm)	Contact Bolts Quantity	Head Size AF (mm)
<b>BSLB-4/16</b>	30	12	2	2.5 (Inner Hexagon)
<b>BSLB-6/25</b>	40	14	2	5 (Inner Hexagon)
<b>BSLB-10/50</b>	40	18	2	10
<b>BSLB-35/95 &amp; BSLB-35/95-REM</b>	50	25	2	10
<b>BSLB-25/150 S-AS &amp; BSLB-25/150 S-AS-REM</b>	70	28	2	13
<b>BSLB-25/150-S-I</b>	74	34	2	8 (Inner Hexagon)
<b>BSLB-95/240 &amp; BSLB-95/240-REM</b>	90	37	4	10

[te.com/energy](http://te.com/energy)

© 2019 TE Connectivity. All Rights Reserved. EPP-3273-DDS-1/19-BSL-Shear-Bolt-Connector-TE

TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

**FOR MORE INFORMATION:  
TE Technical Support Centers**

- USA: + 1 800 327 6996
- Canada: + 1 (905) 475-6222
- Mexico: + 52 (0) 55-1106-0800
- Latin/S. America: + 54 (0) 11-4733-2200
- France: + 33 380 583 200
- UK: + 44 0870 870 7500
- Germany: + 49 896 089 903
- Spain: + 34 916 630 400
- Italy: + 39 333 250 0915
- Benelux: + 32 16 508 695
- Russia: + 7 495-790 790 2-200
- China: + 86 (0) 400-820-6015

