

ES-CAPS

END-SPLICE, ADHESIVE-LINED, FLAME-RETARDED CAP

KEY PRODUCT ATTRIBUTES

- 4:1 Shrink Ratio.
- Highly flame retarded.
- Fluid and moisture-resistant.
- Available in Black and Clear.
- Operating Temperature up to 125°C (with fabric tape to help secure cap).

PRODUCT BENEFITS

- Seals and protects the ingress of moisture to the wire joint and prevents corrosion of the conductor.
- Suitable for Automotive T2 environments.
- UL recognised for use in multiple commercial environments.

ES-Cap Size 0 is the newest addition to the existing Performance Materials ES-Cap portfolio.

The ES-Cap is designed to provide a mechanically tough solution within the operating environment. The ES-Cap, in black, is flame retarded, meaning the product will not propagate a flame, in an extremely high temperature burning situation.

The adhesive layer provides a tight seal, preventing any moisture from entering which could lead to any corrosive problems. Highlighting the importance of applying this product to the capable application. Additionally, the thick adhesive layer can perform highly in environments with extensive temperature ranges.

ES-Caps in general, are easy to install with the use of a hot air gun. However, a suitable alternative would be an infrared heating device.

Furthermore, clear caps allow for see-through installation but are not flame retarded, whereas black caps are. This highlights the different capabilities of both cap options, expanding the potential applications and enabling various customers to be serviced depending on their requirements.

TYPICAL MARKETS



AUTOMOTIVE



ICT




AEROSPACE




INDUSTRIAL

a) Part as supplied



b) part fully recovered



Note: d may be completely blocked by adhesive.

TEMPERATURES

- Minimum Shrink Temperature : 110°C
- Full Recovery Temperature : 135°C
- Operating Temperature : up to 125°C (with fabric tape to help secure cap)

PRODUCT SELECTION INFORMATION - DIMENSIONS IN MM

Size	A ±2.5	B (Min)	D (Min)	d (Max)	Delivery Units (Pack Size)
4:1					
ES-CAP-NO.0-O9-O-40MM	40	25.58	4.57	1.02	MM (10,000pcs)
ES-CAP-NO.1-C1-O-30MM	30	16.78	5.7	1.3	MM (15,000pcs)
ES-CAP-NO.1-C1-O-35MM	35	21.18	5.7	1.3	MM (15,000pcs)
ES-CAP-NO.1-C1-O-40MM	40	25.58	5.7	1.3	MM (15,000pcs)
ES-CAP-NO.1-C1-O-45MM	45	28.45	5.7	1.3	MM (10,000pcs)
ES-CAP-NO.1-C1-O-50MM	50	36.68	5.7	1.3	MM (10,000pcs)
ES-CAP-NO.2-B9-O-35MM	35	21.18	7.4	1.7	MM (10,000pcs)
ES-CAP-NO.2-B9-O-40MM	40	25.58	7.4	1.7	MM (8,000pcs)
ES-CAP-NO.2-B9-O-50MM	50	36.68	7.4	1.7	MM (7,000pcs)
ES-CAP-NO.3-B8-O-35MM	35	21.18	10.8	2.41	MM (5,000pcs)
ES-CAP-NO.3-B8-O-40MM	40	22.48	10.8	2.41	MM (5,000pcs)
ES-CAP-NO.3-B8-O-50MM	50	33.58	10.8	2.41	MM (4,000pcs)

Note: Only standard sizes shown. Other sizes in black and clear are available.

Colour	Standard	Black (-O), clear (-X)
Size Selection	Always order the largest size that will shrink snugly over the component to be covered. Other cap lengths available on request.	
Standard Packaging	In pieces.	
Marking	Caps will be marked with their numbered size (such as ES-1, ES-2 or ES-3)	
Ordering Description	Specify product name, size, colour, and length (for example, ES-CAP-NO.2-B9-O-35MM)	

SPECIFICATIONS AND APPROVALS

Series	UL Approval	TE Specification
ES-Caps	UL224 E85381 (Sizes 0, 1, 2, 3, 4, 5) 600 V, 125°C.	108-120037

Note: Specific information on ES-CAP sizes for UL approval can be found on the E85381 file.

Are you looking to seal out moisture, offer enhanced strain relief, or provide rigorous mechanical protection? Do you need a flame retardant product? Leverage TE's comprehensive portfolio of heat shrink tubing products in a wide range of applications.

Learn more at [TE.com/heatshrinktubing](https://www.te.com/heatshrinktubing)

te.com

TE Connectivity, TE connectivity (logo), EVERY CONNECTION COUNTS, AMP, AMPACT, Bowthorpe EMP, Crompton Instruments, Raychem, SIMEL, UTILUX are trademarks. Other logos, product and Company names mentioned herein may be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this brochure are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

© 2022 TE Connectivity. All Rights Reserved.

01/23