

REV. 0
DCO 142074


COIL: @ 25°C
 RESISTANCE _____ 850 OHMS ± 10%
 NOMINAL VOLTAGE _____ 12.0 VDC
 MUST OPERATE _____ 7.0 VDC

 MUST RELEASE _____ 4.0 VDC MAX, 0.64 VDC MIN.

ENVIRONMENT:
 VIBRATION _____ 10 _____ CPS TO _____ 3000 _____ CPS @ _____ 30 _____ g's
 SHOCK _____ 75 _____ g's _____ 6 _____ MS. DURATION
 TEMPERATURE _____ -65 _____ °C TO _____ +125 _____ °C

NOTES: _____ OPERATE TIME 4.0 MS MAX
 _____ RELEASE TIME 7.5 MS MAX
 _____ CONTACT BOUNCE 1.5 MS MAX

CUSTOMER DATA SHEET



CONTACT RATING: _____ LOW LEVEL TO 1A
 _____ 28 VDC RESISTIVE 100,000 OPERATIONS

DR. PBB 6/6/00

6/6/00

COMMUNICATIONS
INSTRUMENTS, INC.

CUST. _____ QPL
 CUST. NO. M39016/16-019L REV. _____

'JMSD' RELAY

JMSWD-12XL