

TECHNICAL DATASHEET

Doc. No:
TTDS 174 Rev1

Tyco Electronics
EET-...P-4

EET-...P-4 self-adhesive Thermal transfer printable labels.

Label material	Polyester film, yellow		
Adhesive	Permanent pressure sensitive acrylic		
Liner	Glassine		
Thickness:			
Label	0.05 mm ±10%		ASTM D3652
Adhesive	0.033mm ±10%		ASTM D3652
Liner	0.056mm ±10%		ASTM D3652
Peel Adhesion at 23°C	Stainless steel	700 N/m	FTM 1 (72 hour dwell) Average values
Service Temperature	-40°C to +150 °C		
Minimum application temperature	10 °C		
Print permanence	Dry rub		SAE-AS-81531
	Print legible after 30 rubs		
Storage stability	2 years at 21°C and 50% RH		
Printability	Thermal transfer		

Tyco Electronics idento GmbH
Paul-Ehrlich-Straße 23
D-63322 Rödermark
Tel.: 06074/8908-0

Tyco Electronics Identto
ZI de Comboire - 1 rue des
Montagnes de Lans
F-38130 Echirolles
Phone: +33 (0) 476 099 696

Author: M Priddle
Print date: 24-Jun-10
Updated: 8-Jun-10
Page: 1 of 1