



The product described in this document has not been fully tested to ensure conformance to the requirements outlined below. Therefore, TE Connectivity (TE) makes no representation or warranty, express or implied, that the product will comply with these requirements. Further, TE may change these requirements based on the results of additional testing and evaluation. Contact TE Engineering for further details.

### Air Bag 30P Connector

#### 1. Scope

##### 1.1 Content

This specification defines the test method for Air Bag 30P connector, terminal and accessories.

##### 1.2 Qualification

When testing the named products, the following specified specifications and standards shall be used.

All tests have to be done using the applicable inspection plan and product.

##### 1.3 Applied Product

- 85189 Plug assembly
- 85190 Cover assembly
- 85183 Holder housing
- 928999 Terminal
- 85188 Header assembly

#### 2. Applicable Documents

The following documents, if they are related, are sequent to this specification.

In case of conflict between the requirements of this specification and the product drawing or in conflict between the requirements of this specification and the referred documents, this specification has precedence

##### 2.1 TE Connectivity Documents

- 109-1 General Requirements for Test Spec.
- 85189 Customer Drawing (Plug assembly)
- 85190 Customer Drawing (Cover assembly)
- 85183 Customer Drawing (Holder housing)
- 928999 Customer Drawing (Terminal)
- 85188 Customer Drawing (Header assembly)

##### 2.2 HKMC specification

- ES-91500-00 HKMC Connector General Spec.
- MS300-08 HMC Combustibility Spec.
- MS300-34 HMC Smell Spec.
- MS201-02 HMC Material Spec.
- MS300-55 HMC VOCs Spec.

<b>A</b>	<b>RELEASED</b>	<b>JH CHU</b>	<b>13 Mar '20</b>
LTR	Revision Record	DR/CHK	Date

### 3. Requirements

No.	Items	Characteristics			Remark
1	Appearance	No harmful crack, rust, burr, damage, deformation, discoloration etc.			
2	Connector engage and disengage force	18kgf or less			
3	Reverse insertion between housings	It shall not be incorrectly inserted by applying force of 30kgf			
4	Reverse insertion between terminal and housing	5.0kgf or less			
5	Engage force between terminal and housing	1.5kgf or less			
6	Housing locking strength	8kgf or more			
7	Lock release force	Force on release force point of lock part shall be 6kgf or less			
8	Terminal retention force	6kgf or more at secondary locking condition			
9	Terminal engage and disengage force	Engage force: 0.1~0.5kgf, Disengage force: 0.1~0.5kgf			
10	Crimp strength	Satisfy ES91100-00			
11	Voltage drop	Division	Initial	After endurance	
		025	10 mV/A or less	20 mV/A or less	
12	Insulation resistance	Division	Initial	After endurance	
		Non-waterproof	100MΩ or more	1000MΩ or more	
13	Leakage current	Division	Initial	After endurance	
		Non-waterproof	10 μA or less	1 μA or less	
14	High voltage test	There shall be no insulation break.			
15	Temperature rise	Division	After endurance		
		General Connector	30°C or less		
16	Durability test	See Requirement No: 3.1 / 3.11			
17	Engage/Disengage endurance test	See Requirement No: 3.1 / 3.11			
18	Over-current cycle test	See Requirement No: 3.1 / 3.11 / 3.15 @ Basic current: 2.4A			
19	Low temperature test	See Requirement No: 3.1 / 3.11 / 3.12 / 3.13 / 3.15			
20	High/Low temperature shock test	See Requirement No: 3.1 / 3.11			
21	High temperature test	See Requirement No: 3.1 / 3.11			
22	Soldering test	See Requirement No: 3.1			
23	Temperature/Humidity test	See Requirement No: 3.1 / 3.11 / 3.12 / 3.13			
24	Dust test	See Requirement No: 3.11			
25	Oil and liquid test	See Requirement No: 3.1 / 3.11			
26	Sulfur gas test	See Requirement No: 3.1 / 3.11			

27	Complex environment endurance test	See Requirement No: 3.1 / 3.10 / 3.11 / 3.15	
----	------------------------------------	--	--

#### 4. Test conditions

##### 4.1 Specimen

Unless there is specific mention, initial sample should use for the test specimen, and test specimen shall be 5EA or more for each cavity. However, if performance is expected to be clearly satisfactory ever by applying load to the same specimen in turn, it is possible to apply multiple test items to the same specimen. In such case, performance shall be satisfied with each item.

##### 4.2 Laboratory condition

Perform each test at designated temperature and humidity. And control humidity at designated absorption ratio for the connector which uses absorbent resin housing.

Temperature:  $25 \pm 5$  °C, Humidity:  $60 \pm 20\%$