

ECONOMY POWER 2.5 SURFACE MOUNT HEADERS

COMPACT PCB HEADERS SUPPORTING AUTOMATED ASSEMBLY

Economy Power 2.5 (EP 2.5) surface mount technology (SMT) headers are a solution for printed circuit board (PCB) manufacturers using automated assembly to build compact wire-to-board systems. The 2.5 mm pitch EP 2.5 SMT headers are designed to support automated pick-and-place assembly and reflow soldering, helping allow for more efficient PCB manufacturing, as compared to traditional through hole (T/H) headers. These UL and VDE certified headers can help safely mate with existing EP 2.5 connectors and similar 2.5 mm pitch products on the market. Applications for EP 2.5 SMT headers include low power and signal systems in home appliances, HVAC, industrial equipment, and lighting.

ELECTRICAL

- Maximum Current (A): 4.2
- Voltage Rating: 250V AC
- Operating Temperature (°C): -55 to +105

MECHANICAL

- Wire Sizes (AWG): 26-20
- Centerline (mm): 2.5
- Configuration: Single row, vertical, surface mount

STANDARDS & SPECIFICATIONS

- Product Specification: [108-2418](#)
- Application Specification: [114-13315](#)
- UL and VDE Certified
- UL 94 V-0
- IEC 60335-1 Glow Wire Test (GWT*)

FEATURES

- Surface mount technology (SMT) technology supports automatic pick-and-place assembly and reflow soldering
- Reduced risk of connection failure due to solder bridging, as compared to T/H headers
- Mates with existing EP 2.5 connectors and similar 2.5mm pitch products
- Materials meet UL 94 V-0 and IEC 60335-1 glow wire test (GWT*)
- Connectors are UL and VDE certified

ADDITIONAL RESOURCES

For more information about the TE Connectivity Economy Power 2.5 connector offerings and compatible parts, please refer to these resources:

- [Economy Power 2.5 Connectors Product Webpage](#)
- [Economy Power 2.5 Connectors Quick Reference Guide](#)

APPLICATIONS




Appliances



Industrial equipment



HVAC



Automation equipment



Lighting



Automotive

*For more information on glow wire testing please review the white paper [Glow Wire Testing for the Appliance Industry](#) or visit the [Glow Wire Capable Connectors product page](#).

ECONOMY POWER 2.5 SURFACE MOUNT HEADERS

SURFACE MOUNT HEADERS

Number of Positions	Part Number	Flammability Rating
2P	2365497-2	UL 94 V-0 & GWT
3P	2365497-3	
4P	2365497-4	
5P	2365497-5	
6P	2365497-6	
7P	2365497-7	
8P	2365497-8	
9P	2365497-9	
10P	1-2365497-0	

Connect With Us

We make it easy to connect with our experts and are ready to provide the support you need.

Visit te.com/support to chat with a Product Information Specialist.

te.com/economy-power-2.5-connectors

TE Connectivity, TE, TE connectivity (logo) and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

© 2025 TE Connectivity. All Rights Reserved.

06-25