Sealing and Protection for Wire Bundles, Connectors, Terminals and Splices











RayBlock 85 Sealing Kit Easy-to-install grommet and wire bundle sealing for up to 20 wires.



RayBlock 85 Sealing Kit

Designed to provide consistent sealing for cable bundles and the back of connectors. The wires in the bundle are placed within the channels of a specially formulated hot-melt adhesive profile, and then covered by dual wall, heat-shrinkable tubing with a flame-retardant radiation-crosslinked outer wall and hot-melt-adhesive inner wall.

When the tubing is heated, the hot-melt adhesive melts and the tubing shrinks, forcing the molten adhesive to fill all the voids within the wire bundle and tubing. The result is a solid plug of adhesive molded around each wire in the bundle, creating a moisture-resistant seal.

Benefits

- Excellent resistance to all common solvents and acids
- Outstanding vibration resistance
- Excellent electrical insulation
- RoHS/ELV compliant



Protection ProductsHarness Design


Catalog 1654296-3 Revised 10-2012

Heat-Shrinkable Water Blocking Systems for Cable Bundles and Multi-Wire Electrical Connectors

Product Features

RayBlock 85 Sealing Kit

- Continuous operating temperature from −40°C up to +85°C
- Minimum shrink temperature: 80°C
- Minimum full recovery temperature: 110°C
- Flame retarded (ATUM tubing only)
- 4:1 shrink ratio



Product Dimensions

Profile				Tubing			
Number of Channels	h Outside height (nom)	L Length (nom)	W Width (nom)	D (min) Expanded as Supplied	d (max) Recovered after Heating	T (nom)	Ordering Description
	mm	mm	mm	mm	mm	mm	
2	8.5	2.75	8.50	12.00	3.00	34.00	RBK-85 Kit 0102-AX
3	8.5	2.75	12.25	16.00	4.00	33.00	RBK-85 Kit 0103-AX
4	8.5	2.75	16.00	16.00	4.00	44.00	RBK-85 Kit 0104-AX
5	8.5	2.75	21.00	24.00	6.00	34.00	RBK-85 Kit 0105-AX
5	8.5	2.75	21.00	24.00	6.00	23.00	RBK-85 Kit 0305-AX
7	8.5	2.75	27.25	24.00	6.00	65.00	RBK-85 Kit 0107-A0
7	8.5	2.75	27.25	24.00	6.00	23.00	RBK-85 Kit 0607-AX
8	8.5	2.75	31.00	24.00	6.00	47.00	RBK-85 Kit 0208-AX
10	8.5	2.75	38.50	32.00	8.00	55.00	RBK-85 Kit 0510-A0

The selection table is intended for guidance only and individual bundles may well differ in requirement. Special designs may be possible on request to cater for large wires or larger cable bundles. Please contact TE Automotive for further information.

TE Automotive offers a variety of heating tools for the installation of RayBlock 85. The range includes hot-air blowers, infra-red heaters and special automatic heating devices.

Ordering Information

Black (0)	Clear (X)				
Maximum two wires per channel, for wires with maximum outside diameter 2.8 mm. For wires with an outside diameter greater than 2.8 mm, please consult TE Automotive. Standard Packaging: 1000 pcs of profile plus 1000 pcs of tubing per box.					
Specify product name, size and colour (for example RBK-85-Kit-0102-AX)					
Carias	TE				
261162	IE .				
RayBlock 85 Sealing Kit	RW-2101				
	Maximum two wires per cha For wires with an outside dia Standard Packaging: 1000 p Specify product name, size a				



+85 °C -40 °C

Operating Temperature Range



Shrinking Ratio



Shrink Temperature



Flame Retarded



Fluid Resistant